

Prepared for:  
 Scott Swenson  
 Lins Propane Trucks  
 2281 Cedar Street  
 Dighton, MA 02715  
 Phone: 800-252-5467

## S P E C I F I C A T I O N   P R O P O S A L

Description	Weight Front	Weight Rear
<b>Price Level</b>		
M2 PRL-16M (EFF:04/25/17)		
<b>Data Version</b>		
SPECPRO21 DATA RELEASE VER 005		
<b>Interior Convenience/Driver Retention Package</b>		
INTERIOR CONVENIENCE PACKAGE WITH CB PROVISION		
<b>Vehicle Configuration</b>		
M2 106 CONVENTIONAL CHASSIS	5,759	3,503
2019 MODEL YEAR SPECIFIED		
SET BACK AXLE - TRUCK		
STRAIGHT TRUCK PROVISION		
LH PRIMARY STEERING LOCATION		
<b>General Service</b>		
TRUCK CONFIGURATION		
DOMICILED, USA 50 STATES (INCLUDING CALIFORNIA AND CARB OPT-IN STATES)		
PICKUP AND DELIVERY/SHORT HAUL SERVICE		
PETROLEUM BUSINESS SEGMENT		
LIQUID BULK COMMODITY		
TERRAIN/DUTY: 100% (ALL) OF THE TIME, IN TRANSIT, IS SPENT ON PAVED ROADS		
MAXIMUM 8% EXPECTED GRADE		
SMOOTH CONCRETE OR ASPHALT PAVEMENT - MOST SEVERE IN-TRANSIT (BETWEEN SITES) ROAD SURFACE		
MEDIUM TRUCK WARRANTY		
EXPECTED FRONT AXLE(S) LOAD : 10000.0 lbs		



Prepared for:  
 Scott Swenson  
 Lins Propane Trucks  
 2281 Cedar Street  
 Dighton, MA 02715  
 Phone: 800-252-5467

	Description	Weight Front	Weight Rear
	EXPECTED REAR DRIVE AXLE(S) LOAD : 23000.0 lbs		
	EXPECTED GROSS VEHICLE WEIGHT CAPACITY : 33000.0 lbs		
<b>Truck Service</b>	TANK BODY EXPECTED TRUCK BODY LENGTH : 18.0 ft U.S. TANK EXPECTED BODY/PAYLOAD CG HEIGHT ABOVE FRAME "XX" INCHES : 32.0 in		
<b>Engine</b>	CUM L9 300 HP @ 2000 RPM, 2200 GOV RPM, 860 LB/FT @ 1300 RPM	640	30
<b>Electronic Parameters</b>	75 MPH ROAD SPEED LIMIT CRUISE CONTROL SPEED LIMIT SAME AS ROAD SPEED LIMIT PTO MODE ENGINE RPM LIMIT - 1100 RPM PTO RPM WITH CRUISE SET SWITCH - 700 RPM PTO RPM WITH CRUISE RESUME SWITCH - 800 RPM PTO MODE CANCEL VEHICLE SPEED - 5 MPH PTO GOVERNOR RAMP RATE - 250 RPM PER SECOND ONE REMOTE PTO SPEED REMOTE PTO SPEED 1 SETTING - 900 RPM PTO MINIMUM RPM - 700 REGEN INHIBIT SPEED THRESHOLD - 5 MPH		
<b>Engine Equipment</b>	2016 ONBOARD DIAGNOSTICS/2010 EPA/CARB/FINAL GHG17 CONFIGURATION 2008 CARB EMISSION CERTIFICATION - CLEAN IDLE (INCLUDES 6X4 INCH LABEL ON LOWER FORWARD CORNER OF DRIVER DOOR) STANDARD OIL PAN ENGINE MOUNTED OIL CHECK AND FILL ONE PIECE VALVE COVER SIDE OF HOOD AIR INTAKE WITH FIREWALL MOUNTED DONALDSON AIR CLEANER DR 12V 160 AMP 36-SI BRUSHLESS QUADRAMOUNT PAD ALTERNATOR WITH REMOTE BATTERY VOLT SENSE	10	



Prepared for:  
 Scott Swenson  
 Lins Propane Trucks  
 2281 Cedar Street  
 Dighton, MA 02715  
 Phone: 800-252-5467

Description	Weight Front	Weight Rear
(2) ALLIANCE MODEL 1231, GROUP 31, 12 VOLT MAINTENANCE FREE 2250 CCA THREADED STUD BATTERIES		
BATTERY BOX FRAME MOUNTED		
STANDARD BATTERY JUMPERS		
SINGLE BATTERY BOX FRAME MOUNTED LH SIDE UNDER CAB		
WIRE GROUND RETURN FOR BATTERY CABLES WITH ADDITIONAL FRAME GROUND RETURN		
NON-POLISHED BATTERY BOX COVER		
POSITIVE LOAD DISCONNECT WITH CAB MOUNTED CONTROL SWITCH MOUNTED OUTBOARD DRIVER SEAT	8	
POSITIVE AND NEGATIVE POSTS FOR JUMPSTART LOCATED ON FRAME NEXT TO STARTER	2	
CUMMINS TURBOCHARGED 18.7 CFM AIR COMPRESSOR WITH INTERNAL SAFETY VALVE		
STANDARD MECHANICAL AIR COMPRESSOR GOVERNOR		
AIR COMPRESSOR DISCHARGE LINE		
ELECTRONIC ENGINE INTEGRAL SHUTDOWN PROTECTION SYSTEM		
CUMMINS EXHAUST BRAKE INTEGRAL WITH VARIABLE GEOMETRY TURBO WITH ON/OFF DASH SWITCH	20	
RH OUTBOARD UNDER STEP MOUNTED HORIZONTAL AFTERTREATMENT SYSTEM ASSEMBLY WITH RH B-PILLAR MOUNTED VERTICAL TAILPIPE	30	25
ENGINE AFTERTREATMENT DEVICE, AUTOMATIC OVER THE ROAD REGENERATION AND DASH MOUNTED REGENERATION REQUEST SWITCH		
11 FOOT 06 INCH (138 INCH+0/-5.9 INCH) EXHAUST SYSTEM HEIGHT		
STANDARD CURVE BRIGHT UPPER STACK(S)		
RH CURVED VERTICAL TAILPIPE B-PILLAR MOUNTED ROUTED FROM STEP		
13 GALLON DIESEL EXHAUST FLUID TANK	35	10
100 PERCENT DIESEL EXHAUST FLUID FILL		
POLISHED ALUMINUM DIESEL EXHAUST FLUID TANK COVER	15	5
LH MEDIUM DUTY STANDARD DIESEL EXHAUST FLUID TANK LOCATION		
STANDARD DIESEL EXHAUST FLUID PUMP MOUNTING		



Prepared for:  
 Scott Swenson  
 Lins Propane Trucks  
 2281 Cedar Street  
 Dighton, MA 02715  
 Phone: 800-252-5467

Description	Weight Front	Weight Rear
STANDARD DIESEL EXHAUST FLUID TANK CAP		
STAINLESS STEEL AFTERTREATMENT DEVICE/MUFFLER/TAILOPIPE SHIELD		
HORTON DRIVEMASTER ADVANTAGE ON/OFF FAN DRIVE		
AUTOMATIC FAN CONTROL WITHOUT DASH SWITCH, NON ENGINE MOUNTED		
CUMMINS SPIN ON FUEL FILTER		
COMBINATION FULL FLOW/BYPASS OIL FILTER		
1100 SQUARE INCH ALUMINUM RADIATOR	20	
ANTIFREEZE TO -34F, OAT (NITRITE AND SILICATE FREE) EXTENDED LIFE COOLANT		
GATES BLUE STRIPE COOLANT HOSES OR EQUIVALENT		
CONSTANT TENSION HOSE CLAMPS FOR COOLANT HOSES		
RADIATOR DRAIN VALVE		
LOWER RADIATOR GUARD		
PHILLIPS-TEMRO 1000 WATT/115 VOLT BLOCK HEATER	4	
CHROME ENGINE HEATER RECEPTACLE MOUNTED UNDER LH DOOR		
ALUMINUM FLYWHEEL HOUSING		
ELECTRIC GRID AIR INTAKE WARMER		
DELCO 12V 38MT HD STARTER WITH INTEGRATED MAGNETIC SWITCH		
<b>Transmission</b>		
ALLISON 3000 RDS AUTOMATIC TRANSMISSION WITH PTO PROVISION	200	60
<b>Transmission Equipment</b>		
ALLISON VOCATIONAL PACKAGE 223 - AVAILABLE ON 3000/4000 PRODUCT FAMILIES WITH VOCATIONAL MODELS RDS, HS, MH AND TRV		
ALLISON VOCATIONAL RATING FOR ON/OFF HIGHWAY APPLICATIONS AVAILABLE WITH ALL PRODUCT FAMILIES		
PRIMARY MODE GEARS, LOWEST GEAR 1, START GEAR 1, HIGHEST GEAR 6, AVAILABLE FOR 3000/4000 PRODUCT FAMILIES ONLY		
SECONDARY MODE GEARS, LOWEST GEAR 1, START GEAR 1, HIGHEST GEAR 6, AVAILABLE FOR 3000/4000 PRODUCT FAMILIES ONLY		



Prepared for:  
 Scott Swenson  
 Lins Propane Trucks  
 2281 Cedar Street  
 Dighton, MA 02715  
 Phone: 800-252-5467

Description	Weight Front	Weight Rear
PRIMARY SHIFT SCHEDULE RECOMMENDED BY DTNA AND ALLISON, THIS DEFINED BY ENGINE AND VOCATIONAL USAGE		
SECONDARY SHIFT SCHEDULE RECOMMENDED BY DTNA AND ALLISON, THIS DEFINED BY ENGINE AND VOCATIONAL USAGE		
PRIMARY SHIFT SPEED RECOMMENDED BY DTNA AND ALLISON, THIS DEFINED BY ENGINE AND VOCATIONAL USAGE		
SECONDARY SHIFT SPEED RECOMMENDED BY DTNA AND ALLISON, THIS DEFINED BY ENGINE AND VOCATIONAL USAGE		
LOAD BASED SHIFT SCHEDULE AND VEHICLE ACCELERATION CONTROL RECOMMENDED BY DTNA AND ALLISON, THIS DEFINED VOCATIONAL USAGE		
NEUTRAL AT STOP - DISABLED, FUELSENSE - DISABLED		
DRIVER SWITCH INPUT - DEFAULT - NO SWITCHES		
DIRECTION CHANGE ENABLED WITH MULTIPLEXED SERVICE BRAKES - ALLISON 5TH GEN TRANSMISSIONS		
VEHICLE INTERFACE WIRING CONNECTOR WITHOUT BLUNT CUTS, AT BACK OF CAB		
ELECTRONIC TRANSMISSION CUSTOMER ACCESS CONNECTOR MOUNTED BACK OF CAB		
(2) CUSTOMER INSTALLED CHELSEA 277 SERIES PTO'S		
PTO MOUNTING, LH AND RH SIDES OF MAIN TRANSMISSION		
MAGNETIC PLUGS, ENGINE DRAIN, TRANSMISSION DRAIN, AXLE(S) FILL AND DRAIN		
PUSH BUTTON ELECTRONIC SHIFT CONTROL, DASH MOUNTED		
TRANSMISSION PROGNOSTICS - ENABLED 2013		
WATER TO OIL TRANSMISSION COOLER, IN RADIATOR END TANK		
TRANSMISSION OIL CHECK AND FILL WITH ELECTRONIC OIL LEVEL CHECK		
SYNTHETIC TRANSMISSION FLUID (TES-295 COMPLIANT)		
<b>Front Axle and Equipment</b>		
DETROIT DA-F-10.0-3 10,000# FF1 71.5 KPI/3.74 DROP SINGLE FRONT AXLE		



Prepared for:  
 Scott Swenson  
 Lins Propane Trucks  
 2281 Cedar Street  
 Dighton, MA 02715  
 Phone: 800-252-5467

Description	Weight Front	Weight Rear
MERITOR 15X5 Q+ CAST SPIDER CAM FRONT BRAKES, DOUBLE ANCHOR, FABRICATED SHOES		
NON-ASBESTOS FRONT BRAKE LINING		
GUNITE CAST IRON FRONT BRAKE DRUMS		
FRONT BRAKE DUST SHIELDS	5	
FRONT OIL SEALS		
VENTED FRONT HUB CAPS WITH WINDOW, CENTER AND SIDE PLUGS - OIL		
STANDARD SPINDLE NUTS FOR ALL AXLES		
MERITOR AUTOMATIC FRONT SLACK ADJUSTERS		
TRW THP-60 POWER STEERING		
POWER STEERING PUMP		
2 QUART SEE THROUGH POWER STEERING RESERVOIR		
SYNTHETIC 75W-90 FRONT AXLE LUBE		
<b>Front Suspension</b>		
12,000# DUAL TAPERLEAF FRONT SUSPENSION	42	
MAINTENANCE FREE RUBBER BUSHINGS - FRONT SUSPENSION		
FRONT SHOCK ABSORBERS		
<b>Rear Axle and Equipment</b>		
DETROIT DA-RS-23.0-4 23,000# R-SERIES SINGLE REAR AXLE		30
5.56 REAR AXLE RATIO		
IRON REAR AXLE CARRIER WITH STANDARD AXLE HOUSING		
MXL 17T MERITOR EXTENDED LUBE MAIN DRIVELINE WITH HALF ROUND YOKES	20	20
DRIVER CONTROLLED TRACTION DIFFERENTIAL - SINGLE REAR AXLE		20
(1) DRIVER CONTROLLED DIFFERENTIAL LOCK REAR VALVE FOR SINGLE DRIVE AXLE		
BLINKING LAMP WITH EACH MODE SWITCH, DIFFERENTIAL UNLOCK WITH IGNITION OFF, ACTIVE <5 MPH		
MERITOR 16.5X7 Q+ CAST SPIDER CAM REAR BRAKES, DOUBLE ANCHOR, FABRICATED SHOES		
NON-ASBESTOS REAR BRAKE LINING		
BRAKE CAMS AND CHAMBERS ON FORWARD SIDE OF DRIVE AXLE(S) WITH AUXILIARY SUPPORT BRACKETS		2



Prepared for:  
 Scott Swenson  
 Lins Propane Trucks  
 2281 Cedar Street  
 Dighton, MA 02715  
 Phone: 800-252-5467

Description	Weight Front	Weight Rear
CONMET CAST IRON REAR BRAKE DRUMS		
REAR BRAKE DUST SHIELDS		
REAR OIL SEALS		
WABCO TRISTOP D LONGSTROKE 1-DRIVE AXLE SPRING PARKING CHAMBERS		
MERITOR AUTOMATIC REAR SLACK ADJUSTERS		
SYNTHETIC 75W-90 REAR AXLE LUBE		
<b>Rear Suspension</b>		
23,000# 52 INCH VARIABLE RATE MULTI-LEAF SPRING REAR SUSPENSION WITH LEAF SPRING HELPER		110
SPRING SUSPENSION - NO AXLE SPACERS		
STANDARD AXLE SEATS IN AXLE CLAMP GROUP		
<b>Brake System</b>		
AIR BRAKE PACKAGE		
WABCO 4S/4M ABS WITHOUT TRACTION CONTROL		
REINFORCED NYLON, FABRIC BRAID AND WIRE BRAID CHASSIS AIR LINES		
FIBER BRAID PARKING BRAKE HOSE		
STANDARD BRAKE SYSTEM VALVES		
STANDARD AIR SYSTEM PRESSURE PROTECTION SYSTEM		
STD U.S. FRONT BRAKE VALVE		
RELAY VALVE WITH 5-8 PSI CRACK PRESSURE, NO REAR PROPORTIONING VALVE		
BW AD-9 BRAKE LINE AIR DRYER WITH HEATER	20	
AIR DRYER MOUNTED UNDER HOOD		
STEEL AIR BRAKE RESERVOIRS; CUSTOMER ACCEPTS TANKS MOUNTED PERPENDICULAR TO RAIL	10	10
CLEAR FRAME RAILS FROM BACK OF CAB TO FRONT REAR SUSPENSION BRACKET, BOTH RAILS OUTBOARD		
PULL CABLE ON WET TANK, PETCOCK DRAIN VALVES ON ALL OTHER AIR TANKS		
<b>Trailer Connections</b>		
UPGRADED CHASSIS MULTIPLEXING UNIT		
UPGRADED BULKHEAD MULTIPLEXING UNIT		
<b>Wheelbase &amp; Frame</b>		



Prepared for:  
 Scott Swenson  
 Lins Propane Trucks  
 2281 Cedar Street  
 Dighton, MA 02715  
 Phone: 800-252-5467

Description	Weight Front	Weight Rear
5175MM (204 INCH) WHEELBASE		
9/32X3-7/16X10-1/16 INCH STEEL FRAME (7.14MMX255.6MM/0.281X10.06 INCH) 120KSI	90	-30
2025MM (80 INCH) REAR FRAME OVERHANG		
FRAME OVERHANG RANGE: 71 INCH TO 80 INCH	-20	80
CALC'D BACK OF CAB TO REAR SUSP C/L (CA) : 138.45 in		
CALCULATED EFFECTIVE BACK OF CAB TO REAR SUSPENSION C/L (CA) : 135.45 in		
CALC'D FRAME LENGTH - OVERALL : 313.39		
CALC'D SPACE AVAILABLE FOR DECKPLATE : 138.45 in		
CALCULATED FRAME SPACE LH SIDE : 129.57 in		
CALCULATED FRAME SPACE RH SIDE : 123.52 in		
SQUARE END OF FRAME		
FRONT CLOSING CROSSMEMBER		
STANDARD WEIGHT ENGINE CROSSMEMBER		
STANDARD MIDSHIP #1 CROSSMEMBER(S)		
STANDARD REARMOIST CROSSMEMBER		
STANDARD SUSPENSION CROSSMEMBER		
<b>Chassis Equipment</b>		
THREE-PIECE 14 INCH CHROMED STEEL BUMPER WITH COLLAPSIBLE ENDS	30	
FRONT TOW HOOKS - FRAME MOUNTED	15	
BUMPER MOUNTING FOR SINGLE LICENSE PLATE		
FENDER AND FRONT OF HOOD MOUNTED FRONT MUDFLAPS		
GRADE 8 THREADED HEX HEADED FRAME FASTENERS		
TANK BODY 1501 TO 3000 GALLONS		
<b>Fuel Tanks</b>		
50 GALLON/189 LITER RECTANGULAR ALUMINUM FUEL TANK - LH	20	
RECTANGULAR FUEL TANK(S)		
POLISHING OF FUEL/HYDRAULIC TANK(S) WITH PAINTED BANDS		
FUEL TANK(S) FORWARD		
POLISHED STAINLESS STEEL STEP FINISH		
FUEL TANK CAP(S)		





Prepared for:  
 Scott Swenson  
 Lins Propane Trucks  
 2281 Cedar Street  
 Dighton, MA 02715  
 Phone: 800-252-5467

	Description	Weight Front	Weight Rear
	DETROIT FUEL/WATER SEPARATOR WITH WATER IN FUEL SENSOR, HAND PRIMER AND 12 VOLT PREHEATER	-5	
	EQUIFLO INBOARD FUEL SYSTEM		
	HIGH TEMPERATURE REINFORCED NYLON FUEL LINE		
<b>Tires</b>			
	BRIDGESTONE R283A 11R22.5 14 PLY RADIAL FRONT TIRES	6	
	BRIDGESTONE M726ELA 11R22.5 14 PLY RADIAL REAR TIRES		76
<b>Hubs</b>			
	CONMET HIGH CAPACITY PRESET PLUS PREMIUM ALUMINUM FRONT HUBS	-10	
	CONMET PRESET PLUS PREMIUM IRON REAR HUBS		
<b>Wheels</b>			
	ALCOA LVL ONE 88367X 22.5X8.25 10-HUB PILOT 5.79 INSET ALUMINUM DISC FRONT WHEELS	-50	
	ALCOA LVL ONE 88367X ALUMINUM OUTSIDE, ACCURIDE 29637 STEEL INSIDE; 22.5X8.25 10-HUB PILOT DISC REAR WHEELS		-28
	POLISHED FRONT WHEELS; OUTSIDE ONLY		
	POLISHED REAR WHEELS; OUTSIDE OF OUTER WHEELS ONLY		
	FRONT WHEEL MOUNTING NUTS		
	REAR WHEEL MOUNTING NUTS		
	NYLON WHEEL GUARDS BETWEEN REAR DUAL WHEELS ONLY		
<b>Cab Exterior</b>			
	106 INCH BBC FLAT ROOF ALUMINUM CONVENTIONAL CAB		
	AIR CAB MOUNTING		
	NONREMOVABLE BUGSCREEN MOUNTED BEHIND GRILLE		
	LH AND RH GRAB HANDLES		
	HOOD MOUNTED CHROMED PLASTIC GRILLE		
	CHROME HOOD MOUNTED AIR INTAKE GRILLE		
	FIBERGLASS HOOD		
	DUAL 26 INCH RECTANGULAR POLISHED ALUMINUM AIR HORNS ROOF MOUNTED	8	
	SINGLE ELECTRIC HORN		



Prepared for:  
 Scott Swenson  
 Lins Propane Trucks  
 2281 Cedar Street  
 Dighton, MA 02715  
 Phone: 800-252-5467

Description	Weight Front	Weight Rear
DUAL HORN SHIELDS		
DOOR LOCKS AND IGNITION SWITCH KEYED THE SAME		
REAR LICENSE PLATE MOUNT END OF FRAME		
SWITCH, INDICATOR LIGHT AND WIRING FOR (2) CUSTOMER FURNISHED BEACONS		
INTEGRAL HEADLIGHT/MARKER ASSEMBLY WITH CHROME BEZEL		
LED AERODYNAMIC MARKER LIGHTS		
DAYTIME RUNNING LIGHTS		
OMIT STOP/TAIL/BACKUP LIGHTS AND PROVIDE WIRING WITH SEPARATE STOP/TURN WIRES TO 4 FEET BEYOND END OF FRAME		-5
STANDARD FRONT TURN SIGNAL LAMPS		
SWITCH, INDICATOR LIGHT AND APPROXIMATELY 10 FEET OF WIRE ON CHASSIS RH BACK OF CAB FOR CUSTOMER FURNISHED UTILITY LIGHT(S)		
DUAL WEST COAST BRIGHT FINISH HEATED MIRRORS WITH LH AND RH REMOTE		
DOOR MOUNTED MIRRORS		
102 INCH EQUIPMENT WIDTH		
LH AND RH 8 INCH BRIGHT FINISH CONVEX MIRRORS MOUNTED UNDER PRIMARY MIRRORS		
RH DOWN VIEW MIRROR		
STANDARD SIDE/REAR REFLECTORS		
RH AFTERTREATMENT SYSTEM CAB ACCESS WITH POLISHED DIAMOND PLATE COVER		
ELECTRIC HORN WARNING SYSTEM FOR PARK BRAKE NOT SET WITH DOOR OPEN AND ALL IGNITION KEY POSITIONS		
COMPOSITE EXTERIOR SUN VISOR	10	
63X14 INCH TINTED REAR WINDOW		
TINTED DOOR GLASS LH AND RH WITH TINTED NON-OPERATING WING WINDOWS		
RH AND LH ELECTRIC POWERED WINDOWS	4	
LOWER RH DOOR WINDOW WITH FRESNEL LENS	7	
TINTED WINDSHIELD		
2 GALLON WINDSHIELD WASHER RESERVOIR WITHOUT FLUID LEVEL INDICATOR, FRAME MOUNTED		

**Cab Interior**



Prepared for:  
 Scott Swenson  
 Lins Propane Trucks  
 2281 Cedar Street  
 Dighton, MA 02715  
 Phone: 800-252-5467

Description	Weight Front	Weight Rear
OPAL GRAY VINYL INTERIOR		
MOLDED PLASTIC DOOR PANEL WITHOUT VINYL INSERT WITH ALUMINUM KICKPLATE LOWER DOOR		
MOLDED PLASTIC DOOR PANEL WITHOUT VINYL INSERT WITH ALUMINUM KICKPLATE LOWER DOOR		
BLACK MATS WITH SINGLE INSULATION		
FORWARD ROOF MOUNTED CONSOLE WITH UPPER STORAGE COMPARTMENTS WITHOUT NETTING		
IN DASH STORAGE BIN		
CENTER STORAGE CONSOLE MOUNTED ON BACKWALL	20	
LH DOOR MAP POCKET		
(2) CUP HOLDERS LH AND RH DASH		
GRAY/CHARCOAL FLAT DASH		
5 LB. FIRE EXTINGUISHER	10	
FIRST AID KIT	2	
HEATER, DEFROSTER AND AIR CONDITIONER		
STANDARD HVAC DUCTING		
MAIN HVAC CONTROLS WITH RECIRCULATION SWITCH		
STANDARD HEATER PLUMBING WITH BALL SHUTOFF VALVES		
DENSO HEAVY DUTY AIR CONDITIONER COMPRESSOR		
BINARY CONTROL, R-134A		
STANDARD INSULATION		
SOLID-STATE CIRCUIT PROTECTION AND FUSES		
12V NEGATIVE GROUND ELECTRICAL SYSTEM		
DOMED DOOR ACTIVATED LH AND RH, DUAL READING LIGHTS, FORWARD CAB ROOF		
LH AND RH ELECTRIC DOOR LOCKS		
(2) 12 VOLT POWER RECEPTACLES MOUNTED IN DASH		
TRIANGULAR REFLECTORS WITHOUT FLARES	10	
BASIC HIGH BACK AIR SUSPENSION DRIVER SEAT WITH MECHANICAL LUMBAR AND INTEGRATED CUSHION EXTENSION	30	
BASIC HIGH BACK NON SUSPENSION PASSENGER SEAT		
LH AND RH INTEGRAL DOOR PANEL ARMRESTS		



Prepared for:  
 Scott Swenson  
 Lins Propane Trucks  
 2281 Cedar Street  
 Dighton, MA 02715  
 Phone: 800-252-5467

Description	Weight Front	Weight Rear
BLACK CORDURA PLUS CLOTH DRIVER SEAT COVER		
BLACK CORDURA PLUS CLOTH PASSENGER SEAT COVER		
BLACK SEAT BELTS		
ADJUSTABLE TILT AND TELESCOPING STEERING COLUMN	10	
4-SPOKE 18 INCH (450MM) STEERING WHEEL		
DRIVER AND PASSENGER INTERIOR SUN VISORS		
<b>Instruments &amp; Controls</b>		
WOODGRAIN DRIVER INSTRUMENT PANEL		
WOODGRAIN CENTER INSTRUMENT PANEL		
BLACK GAUGE BEZELS		
LOW AIR PRESSURE INDICATOR LIGHT AND AUDIBLE ALARM		
2 INCH PRIMARY AND SECONDARY AIR PRESSURE GAUGES		
INTAKE MOUNTED AIR RESTRICTION INDICATOR WITHOUT GRADUATIONS		
ELECTRONIC CRUISE CONTROL WITH SWITCHES IN LH SWITCH PANEL		
KEY OPERATED IGNITION SWITCH AND INTEGRAL START POSITION; 4 POSITION OFF/RUN/START/ACCESSORY		
ICU3S, 132X48 DISPLAY WITH DIAGNOSTICS, 28 LED WARNING LAMPS AND DATA LINKED		
HEAVY DUTY ONBOARD DIAGNOSTICS INTERFACE CONNECTOR LOCATED BELOW LH DASH		
2 INCH ELECTRIC FUEL GAUGE		
PROGRAMMABLE RPM CONTROL - ELECTRONIC ENGINE		
ELECTRICAL ENGINE COOLANT TEMPERATURE GAUGE		
2 INCH TRANSMISSION OIL TEMPERATURE GAUGE		
ENGINE AND TRIP HOUR METERS INTEGRAL WITHIN DRIVER DISPLAY		
CUSTOMER FURNISHED AND INSTALLED PTO CONTROLS		
ELECTRIC ENGINE OIL PRESSURE GAUGE		
OVERHEAD INSTRUMENT PANEL		



Prepared for:  
 Scott Swenson  
 Line Propane Trucks  
 2281 Cedar Street  
 Dighton, MA 02715  
 Phone: 800-252-5467

Description	Weight Front	Weight Rear
AM/FM/WB WORLD TUNER RADIO WITH CD PLAYER, BLUETOOTH, IPOD INTERFACE, USB AND AUXILIARY INPUTS, J1939 DASH MOUNTED RADIO (2) RADIO SPEAKERS IN CAB AM/FM ANTENNA MOUNTED ON FORWARD LH ROOF POWER AND GROUND WIRING PROVISION OVERHEAD CB WIRING ONLY TO ROOF/OVERHEAD CONSOLE; NO MOUNTING PROVISION ELECTRONIC MPH SPEEDOMETER WITH SECONDARY KPH SCALE, WITHOUT ODOMETER STANDARD VEHICLE SPEED SENSOR ELECTRONIC 3000 RPM TACHOMETER NO VEHICLE PERFORMANCE MONITOR	10	
IGNITION SWITCH CONTROLLED ENGINE STOP DIGITAL VOLTAGE DISPLAY INTEGRAL WITH DRIVER DISPLAY SINGLE ELECTRIC WINDSHIELD WIPER MOTOR WITH DELAY AND ARCTIC TYPE BLADES MARKER LIGHT SWITCH INTEGRAL WITH HEADLIGHT SWITCH ONE VALVE PARKING BRAKE SYSTEM WITH DASH VALVE CONTROL AUTONEUTRAL AND WARNING INDICATOR SELF CANCELING TURN SIGNAL SWITCH WITH DIMMER, WASHER/WIPER AND HAZARD IN HANDLE INTEGRAL ELECTRONIC TURN SIGNAL FLASHER WITH HAZARD LAMPS OVERRIDING STOP LAMPS	-5	

**Design**

PAINT: ONE SOLID COLOR

**Color**

CAB COLOR A: N0006EA WHITE ELITE SS  
 BLACK, HIGH SOLIDS POLYURETHANE CHASSIS PAINT  
 POWDER WHITE (N0006EA) REAR  
 WHEELS/RIMS (PKWHT21, TKWHT21, W, TW)  
 SUNVISOR PAINTED SAME AS CAB COLOR A  
 STANDARD E COAT/UNDERCOATING

**Certification / Compliance**



Prepared for:  
 Scott Swenson  
 Linc Propane Trucks  
 2281 Cedar Street  
 Dighton, MA 02715  
 Phone: 800-252-5467

Description	Weight Front	Weight Rear
U.S. FMVSS CERTIFICATION, EXCEPT SALES CABS AND GLIDER KITS		
<b>Secondary Factory Options</b>		
CORPORATE PDI CENTER IN-SERVICE ONLY		

**TOTAL VEHICLE SUMMARY**

**Weight Summary**

	Weight Front	Weight Rear	Total Weight
Factory Weight*	7032 lbs	3918 lbs	10950 lbs
Dealer Installed Options	0 lbs	0 lbs	0 lbs
<b>Total Weight*</b>	<b>7032 lbs</b>	<b>3918 lbs</b>	<b>10950 lbs</b>

**Extended Warranty**

TOWING: 1 YEAR/UNLIMITED MILES/KM EXTENDED TOWING  
 COVERAGE \$550 CAP FEX APPLIES

**Dealer Installed Options**

	Weight Front	Weight Rear
PDI AUTO NEUTRAL WIRING	0	0
<b>Total Dealer Installed Options</b>	<b>0 lbs</b>	<b>0 lbs</b>

(+) Weights shown are estimates only.

If weight is critical, contact Customer Application Engineering.



Prepared for:  
Scott Swenson  
Lins Propane Trucks  
2281 Cedar Street  
Dighton, MA 02715  
Phone: 800-252-5467

