



Hunter Truck Sales (H520)
 100 Hunters Way
 Smithfield, Pennsylvania 15478

Lin's Propane Trucks
 2281 Cedar St
 Dighton, Massachusetts 02715
 United States of America

Andy Keller
 Phone:
 Email: akeller@huntertrucksales.com

Scott Swensen
 Phone:
 Email:

Vehicle Summary

	Unit		Chassis	
Model:		Model 337	Fr Axle Load (lbs):	10000
Type:		Full Truck	Rr Axle Load (lbs):	23000
Description 1:		LINS PX7 Disc	G.C.W. (lbs):	42000
Description 2:		PX7 Disc 632011		
	Application		Road Conditions:	
Intended Serv.:		Tanker, Liquid Bulk	Class A (Highway)	100
Commodity:		Petroleum Products	Class B (Hwy/Mtn)	0
			Class C (Off-Hwy)	0
	Body		Class D (Off-Road)	0
Type:		Tank	Maximum Grade:	6
Length (ft):		20	Wheelbase (in):	208
Height (ft):		13.5	Overhang (in):	81.8
Max Laden Weight (lbs):		1000	Fr Axle to BOC (in):	69.8
			Cab to Axle (in):	138.2
	Trailer		Cab to EOF (in):	220
No. of Trailer Axles:		0	Overall Comb. Length (in):	328
Type:				
Length (ft):		0	Special Req.	
Height (ft):		0		
Kingpin Inset (in):		0		
Corner Radius (in):		0		
	Restrictions			
Length (ft):		40		
Width (in):		102		
Height (ft):		13.5		

Approved by: _____

Date: _____

Note: All sales are F.O.B. designated plant of manufacture.



Sales Code	Std/Opt	Description	\$ List	Weight
Base Model				
0003371	S	Model 337 The Peterbilt Model 337 is built to take on the big jobs. That's why it's available as a Class 7 truck or tractor with a GVW up to 33,000 lbs. With a full range of suspensions and in an all-wheel-drive configuration, the 337 delivers an ideal match for applications such as wrecker, tanker, beverage delivery, municipal utilities – just about any job you can throw at it.	94,048	10,070
0091130	O	Petroleum Products	0	0
0093020	O	Tanker, Liquid Bulk General freight (linehaul) service using a liquid bulk tanker body or tanker trailer.	0	0
0095150	O	Tank A truck equipped to transport liquefied loads, dru bulk cargo, or gases. May be insulated or non-insulated; pressurized or non-pressurized; and designed for single or multiple loads (often by means of internal divisions in their tank).	0	0
0098170	S	United States Registry Canadian Registry Package Requires Air Conditioning Excise Tax Canada, Speedometer to be KPH ipo MPH, Daytime Running Lights and Rubber Battery Pad in Bottom of Battery Box.	0	0
Configuration				
0200700	S	Not Applicable Secondary Manufacturer	0	0
Frame & Equipment				
0515020	O	10-5/8" Steel Rails 286-325" 10.625 x 3.45 x .313 Dimension, 1,776,000 RBM; Yield Strength: 120,000 psi. Section Modulus: 14.8 cubic inches. Weight: 1.44 lbs/inch pair	45	253
0612170	O	208" Wheelbase	0	0
0613090	O	Three-Piece Crossmembers	695	3
0633405	O	Additional Frame Drilling	502	0
0644090	S	EOF Square without Crossmember For use with body builder installed crossmember.	0	0
0651090	S	Omit Rear Mudflaps and Hangers	0	0
Front Axle & Equipment				
1011830	S	Dana Spicer E1002IL 10,000 lb, 3.5 in. Drop Axle is designed for applications with a gross axle weight rating (GAWR) of 10,000 pounds. The axles have exclusive one-piece forged design knuckle including steer arm, tie rod arm and spindle. This feature helps in greater durability and reduced maintenance.	0	0

Price Level: January 1, 2019

Deal: LINS PX7 Disc

Printed On: 6/10/2019 12:39:41 PM

Date: June 10, 2019

Quote Number: QUO-499527-W0P3B2



Sales Code	Std/ Opt	Description	\$ List	Weight
1111180	S	Taper Leaf Springs, Shocks 10,000 lb	0	0
1233100	O	Power Steering TRW THP60 TRW THP60 Power Steering is for use with 10,000 to 13,200 lb. axle ratings. Glidekote splines on steering shaft extend service life of components.	88	-19
1250180	O	Power Steering Reservoir Frame Mounted The power steering reservoir is a steering system that eases drivability by applying hydraulic pressure to the steering gear.	0	0
1353555	O	PHP10 Aluminum PreSet Hubs Air Disc	914	0
1380240	O	Dana Spicer Wide Track IPO Standard Dana Spicer wide track front axles offer added stability and deliver greater turn angles. 71in KPI IPO 69in for E1202, E1322, E1462, D2000F front axles.	33	15
1380290	O	Bendix Air Disc Front Brakes Bendix air disc front brakes use a floating caliper design to provide foundation braking on all axles and complies with reduced stopping distance regulations.	-209	30
Rear Axle & Equipment				
1513280	O	Dana Spicer S23-172, 23,000lb	1,274	250
1616360	O	PHP10 Aluminum PreSet Hubs	92	0
1632650	O	Long Stroke Parking Brakes, Drive Axle(s)	20	20
1680500	S	SBM Valve Full trucks require a spring brake modulation (SBM) system for emergency braking application. This system requires an SBM valve and a relay valve with spring brakes on the rear axles. The SBM valve allows the foot valve to operate the rear axle spring brakes if a failure exists in the rear air system.	0	0
1680795	O	Diff Lock, Single Drive Axle with Speed Interlock	875	30
1680950	S	Stability System Not Selected Or Not Available	0	0
1681337	S	Single Drive Axle (Model 337)	0	0
1682430	S	Anti-Lock Braking System (ABS) 4S4M ABS-6. Includes air braking system.	0	0
1684200	S	Synthetic Axle Lubricant All Axles Peterbilt heavy duty models include Fuel Efficient Cognis EMGARD FE75W-90 which provides customers performance advantages over current synthetic lubricants with reduced gear wear and extended maintenance intervals, resulting in increased uptime. In addition, the lubricant provides improved fluid flow to protect gears in extreme cold conditions and withstand the stress from high temperatures, extending component life.	0	0

Price Level: January 1, 2019

Deal: LINS PX7 Disc

Printed On: 6/10/2019 12:39:41 PM

Date: June 10, 2019

Quote Number: QUO-499527-W0P3B2



Sales Code	Std/Opt	Description	\$ List	Weight
1687080	O	Air Disc Rear Brakes, Single Drive Axle	1,997	0
1706140	O	Ratio 6.14 Rear Axle	0	0
1816020	O	Reyco 79KB Multi Leaf 23,000 Lb	47	30

Engine & Equipment

2073407	O	PACCAR PX-7 325@2400 GOV@2600 750@1800 Performance (2017 Emissions) Includes alum flywheel housing, cruise control, and J1939 provisions (provides an interface point for the Electronic Service Analysis-ESA and other PACCAR approved diagnostic tools). Chevron Delo LE SAE 10W30 engine oil is specially formulated for new low emissions engines. Magnetic engine oil drain plug captures and holds any metal fragments in engine oil to extend service life. N21320 N205 120...Standard Maximum Speed Limit N21470 P062 NO....Cruise Control Auto Resume (N21480 P068 NO....Auto Engine Brake in Cruise N21450 P026 NO....Gear Down Protection (P026) N21440 P015 NO....Engine Protection Shutdown (N21350 P001 75....Maximum Accelerator Pedal Ve N21370 P059 75....Maximum Cruise Speed (P059) N21590 P230 YES...Enable Hot Ambient Automatic N21530 P233 YES...Enable Impending Shutdown Wa N21540 P234 60....Timer For Impending Shutdown N21460 P046 1400..Max PTO Speed (P046) N21520 P030 5.....Timer Setting (P030) N21570 P031 NO....Idle Shutdown Manual Overrul N21610 P172 40....Low Ambient Temperature Thre N21630 P171 80....High Ambient Temperature Thr N21510 P520 YES...Enable Idle Shutdown Park Br N21430 N201 0.....Reserve Speed Limit Offset (N21410 N202 0.....Maximum Cycle Distance (N202 N21400 N203 252...Reserve Speed Function Reset N21420 N206 10....Maximum Active Distance (N20 N21340 P112 120...Hard Maximum Speed Limit (P1 N21550 P516 35....Engine Load Threshold (P516) N21620 P173 60....Intermediate Ambient Tempera N21330 N207 0.....Expiration Distance (N207) N21500 N209 0.....Expiration Distance (N209)	-2,042	-540
2091310	O	Engine Idle Shutdown Timer Disabled	0	0
2091372		Eff EIST NA Expiration Miles	0	0
2091640		Effective VSL Setting NA	0	0
2140150	O	Remote PTO and Throttle Provision	17	0
2140200	S	CARB Engine Idling Compliance	0	0

Price Level: January 1, 2019

Deal: LINS PX7 Disc

Printed On: 6/10/2019 12:39:41 PM

Date: June 10, 2019

Quote Number: QUO-499527-W0P3B2



Sales Code	Std/ Opt	Description	\$ List	Weight
		PACCAR PX-7, PX-9 and MX, Cummins X15 and ISX diesel engines will include the required factory installed serialized sticker on the drivers door to identify them as meeting the NOx idling standard.		
2513060	S	PACCAR 160 Amp Alternator, Brushed PACCAR 160 AMP alternator, brushed producing 160 Amps at road speed and 100 Amps at idle.	0	0
2521090	O	Immersion Type Block Heater 110-120V Standard location for 2.1M and 1.9M models is left-hand under cab, Model 520 is in bumper, and for Model 220 it is at the driver step. Plug includes a weather-proof cover that protects the receptacle. This pre-heater keeps the coolant in the engine block from freezing when the engine is not running.	82	2
2522110	S	PACCAR 12V Starter, N/A PACCAR MX Engines PACCAR 12-volt electrical system. With centralized power distribution incorporating plug-in style relays. Circuit protection for serviceability, 12-volt light system w/circuit protection circuits number & color coded.	0	0
2538030	S	2 PACCAR Premium 12V Starting Batteries 2000 CCA Threaded stud type terminal. Stranded copper battery cables are double aught (00) or larger to reduce resistance.	0	0
2539740	O	Kissing Battery Disconnect Switch, 300 amp Mounted on battery box	183	3
2621090	S	DM Advantage ON/OFF Fan Clutch Horton DM Advantage Two-Speed Fan Clutch On/Off for heavy-duty, medium-duty and a variety of off-highway equipment.	0	0
2723210	S	18.7 CFM Air Compressor N/A X15. Furnished on engine. Teflon lined stainless steel braided compressor discharge line.	0	0
2812210	O	VGT Exhaust Brake (Variable Geometry Turbo). Provides approximately 90-100 HP of retardation and is part of the turbocharger.	316	0
2921160	S	Spin-On Fuel/Water Separator	0	0
2921210	S	No Fluid Heat Option for Fuel Filter	0	0
2921320	O	12V Heat for Fuel Filter	58	0
3114270	S	High Efficiency Cooling System Cooling module is a combination of steel and aluminum components, with aluminum connections to maximize performance and cooling capability. Silicone radiator & heater hoses enhance value, durability, & reliability. Constant tension band clamps reduce leaks. ClimaTech extended life coolant extends maintenance intervals which reduces maintenance costs. Anti-freeze effective to -30 degrees F helps protect the engine. Low coolant level sensor warns of low coolant condition to prevent engine damage. Radiator Size by Model: 579/367 FEPTO 1325 sq in, 567/365/367: 1440 sq in, 365 FEPTO: 1184 sq in, 389/367 HH: 1669 sq in, 348: 1000 sq in, 520: 1242 sq in.	0	0
3211120	S	Radial Seal, Dry Type Air Cleaner, Frontal Air Intake. Molded rubber air intake connections with lined stainless steel clamps seal to prevent contaminants in air intake.	0	0

Price Level: January 1, 2019

Deal: LINS PX7 Disc

Printed On: 6/10/2019 12:39:41 PM

Date: June 10, 2019

Quote Number: QUO-499527-W0P3B2



Sales Code	Std/ Opt	Description	\$ List	Weight
3365270	O	Exhaust Single RH Side of Cab DPF/SCR right-hand Under Cab (2017).	392	29
3381770	O	Curved Tip Standpipe(s)	42	0
3387870	O	24" Ht, 5" Dia Chrome, Clear Coat Standpipe(s)	496	0

Transmission & Equipment

4052110	O	Allison 3000 RDS-P Transmission, Gen 5 Rugged Duty Series. Includes Rear Transmission Support except on MX engines, TranSynd Automatic Transmission Fluid, and Water-Oil Heat Exchange. Also includes features that monitor the transmission fluid, filter and clutch condition. Will display percent life remaining for the transmission fluid, filter and clutches on the shift selector. This information may be displayed using the Mode and Up and Down buttons. A wrench icon will also be included to indicate when the transmission fluid, filter or clutches need servicing. Suited for vehicles operating on/off highway and/or requiring PTO operation. Forward ratios: 1st-3.49, 2nd-1.86, 3rd-1.41, 4th-1.00, 5th-0.75, 6th-0.65. Reverse ratios: DR-(5.03).	10,433	195
4210320	O	1710 HD Driveline, 2 Midship Bearings	635	100
4250420	U	ALLISON 5TH GEN RDS, PKG 223	0	0
4252170	O	Auto Neutral Activates With Parking Brake Auto Neutral helps improve jobsite safety by reducing the possibility of the truck moving due to throttle application.	16	0
4252890	O	Allison FuelSense 2.0 Not Desired	0	0
4252950	O	Omit Allison Neutral At Stop	0	0
4256640	O	Allison 6-Speed Configuration, Close Ratio Gears 3000 Series Transmissions	0	0
4256920	O	Dash Mounted Push Button Shifter Available with Allison transmissions	628	0

Air & Trailer Equipment

4510320	S	Bendix AD-IS Air Dryer, Heater Coalescing filter	0	0
4540420	S	Nylon Chassis Hose	0	0
4543320	S	Steel Painted Air Tanks All air tanks are steel with painted finish except when Code 4543330 Polish Aluminum Air Tanks is also selected (then exposed air tanks outside the frame rails will be polished aluminum). Peterbilt will determine the optimal size and location of required air tanks. Narratives requesting a specific air tank size or location will not be accepted for factory installation. See ECAT to determine number or location of air tanks installed.	0	0
4543330	O	Aluminum Polished Air Tanks Outside Frame Rails	333	0

Price Level: January 1, 2019

Deal: LINS PX7 Disc

Printed On: 6/10/2019 12:39:41 PM

Date: June 10, 2019

Quote Number: QUO-499527-W0P3B2



Sales Code	Std/ Opt	Description	\$ List	Weight
		Exposed air tanks outside the frame rails will be polished aluminum. Air tanks mounted inside the frame rails or covered by other components will be either painted aluminum (4543340) or painted steel (4543320) air tanks depending on air tank option selected.		
Tires & Wheels				
5069600	O	FF: BR 14ply 11R22.5 R268 Ecopia R268 tread is not a Line Haul tire and is only for Pickup and Delivery or Regional use. Diameter = 41.5 inches; SLR = 19.3 inches	70	8
5169310	O	RR: BR 16ply 11R22.5 M799 Diameter = 42.0 inches; SLR = 19.5 inches	592	36
5190004	O	Code-rear Tire Qty 04	0	0
5221740	O	FF: Alcoa 883677 22.5X8.25 Clean Buff Finish Aluminum	337	-44
5321740	O	RR: Alcoa 883677 22.5X8.25 Clean Buff Finish Aluminum	674	-88
5390004	O	Code-rear Rim Qty 04	0	0
Fuel Tanks				
5532040	O	23" Aluminum 50 Gallon Fuel Tank RH BOC Paddle handle filler cap with threadless filler neck. Top draw fuel plumbing reduces chance of introducing air into the fuel system during low fuel level conditions due to the central placement of fuel pickup tube. Wire braid fuel lines increase durability & reduce potential for leaks.	-62	-126
5603050	O	Location RH BOC 50 Gallon	0	0
5652890	S	DEF Tank Mounted LH BOC Models 220 and 520 mounted left-hand cab fender	0	0
5652990	S	Standard DEF to Fuel Ratio 2:1 Or Greater	0	0
5655019	O	DEF Tank Small	-135	0
Battery Box & Bumper				
6010030	O	Aluminum Battery Box LH Under Cab, Non-Slip Step Includes diamond pattern block shaped cover in traditional/vocational models and a smooth finish tapered cover on aerodynamic models	180	-55
6040550	S	Aftertreatment Aluminum Non-Slip Cab Entry Aftertreatment right-hand under cab step. DPF/SCR for diesel engines, catalyst for natural gas engines. On Models 579 specifying chassis fairings, the box is aerodynamic.	0	0
6121200	O	Steel Styled Aero Bumper Chrome Two tow pins	266	0
Cab & Equipment				
6510110	S	Alum Cab 108in BBC Metton Hood w/Bright Crown	0	0

Price Level: January 1, 2019

Deal: LINS PX7 Disc

Printed On: 6/10/2019 12:39:41 PM

Date: June 10, 2019

Quote Number: QUO-499527-W0P3B2



Sales Code	Std/ Opt	Description	\$ List	Weight
		Includes view window RH door and convex mirror over RH door.		
6540160	O	Thermal Insulation Package in Cab Includes thick, closed-cell foam in floor, special mylar-faced foam in walls and roof structure.	19	2
6911700	S	Peterbilt UltraRide Driver Seat	0	0
6921700	O	Peterbilt UltraRide Passenger Seat	-163	0
6930580	O	Drivers Armrests - LH & RH	69	4
6930590	O	Passenger Armrest - LH only Required with Evolution LX seats, optional with Evolution ST Seats.	40	2
6930800	O	Black Seat Color IPO Standard Color	0	0
6939400	O	Air Ride Driver	195	0
6939420	S	High Back Driver	0	0
6939470	S	Vinyl Driver	0	0
6939510	S	Non-Air Ride Passenger	0	0
6939540	S	Low Back Passenger	0	0
6939570	S	Vinyl Passenger	0	0
7001520	O	Adjustable Steering Column - Tilt/Telescope	113	11
7001620	S	Steering Wheel With Peterbilt Logo Steering Wheel with embossed Peterbilt logo over horn button.	0	0
7036120	S	Interior Grey/Black Includes rugged charcoal instrument panels, glare-resistant gray dash, black bezels on gauges, (2) power ports, monochromatic molded door pads with durable in-mold color, gray molded back wall, 18 inch 4-spoke soft-touch steering wheel, soft-touch steering column cover, power lift passenger window, extruded rubber floor covering, header-mounted dome light, foot well lighting, integrated "dead pedal", (4) inside entry grab handles, (2) inside sunvisors, (2) coat hooks, (2) cup holders and map bin in dash.	0	0
7210390	O	Cab Rear Corner Windows - Standard Tint	544	4
7210430	O	Extended Rear Window ipo Std Window-Day Cab The extended rear window protrudes two inches more than the standard conventional rear cab window. Take this into consideration when determining your loadspace.	67	18
7210540	S	Day Cab Rear Window	0	0
7230060	S	1-Piece Curved Windshield	0	0

Price Level: January 1, 2019

Deal: LINS PX7 Disc

Printed On: 6/10/2019 12:39:41 PM

Date: June 10, 2019

Quote Number: QUO-499527-W0P3B2



Sales Code	Std/Opt	Description	\$ List	Weight
7322010	S	Combo Fresh Air Heater/Air Conditioner With radiator mounted condenser, dedicated side window defrosters, Bi-Level Heater/Defroster Controls, 54,500 BTU/HR, and silicone heater hoses.	0	0
7410040	O	Outside Sunvisor - Stainless Steel Not available with 2.1M high roof sleeper.	193	4
7511010	O	Stainless Steel Mirrors 7x16 with Heat Element Right Click on Option to see Picture in Product Portfolio.	72	2
7560850	O	(2) Convex 8 Inch SSTL Mirrors Center mounted under mirror bracket. If rear view mirrors are heated, the convex mirrors will be heated. Option includes dual door stops.	240	4
7564110	O	Power Package Includes power door locks and power windows.	343	0
7620620	O	(2) Air Horns 24.5" Chrome - Round w/Horn Shields	466	16
7725710	O	Standard Speaker Package For Cab (2) Speakers	118	4
7725715	O	ConcertClass Without CD, Includes BT Phone and Audio, AM/FM, WB, USB and MP3.	324	10
7782230	O	Radio Antenna Mounted Logger Style Antenna Mounted LH on BOC In Place of Center Roof position on Conventional Models. Models 579 and 567 Antenna Mounted LH Roof In Place Of Center Roof position.	24	2
7850015	O	Rear Wall Deep Record/Map Pocket	141	2
7850210	O	Plug-In Auto Reset Circuit Breaker in place of fuses in junction box.	40	0
7851480	S	Peterbilt Electric Windshield Wipers With Intermittent Feature.	0	0
7900090	O	Triangle Reflector Kit, Ship Loose Florescent triangle emergency road flares are designed to meet and exceed all DOT standards.	17	13
7900270	O	Fire Extinguisher, Cab Mounted Hazmat approved UL listed/rated ABC	54	8
8011400	O	Main Transmission Oil Temperature Gauge Located in Driver Information Display	13	0
8021380	S	Air Restriction Indicator Mounted on air cleaner, intake piping, or firewall	0	0
8071340	O	Bright Bezel Gauges	50	0
8071870	S	Main Instrumentation Panel, Graphics Display Includes speedometer with trip odometer, tachometer with hourmeter and outside air temperature display, voltmeter, engine oil pressure, engine coolant temperature, fuel level, primary and secondary air pressure gauges. Includes standard warning light package: high water temperature, low oil pressure, and low air pressure warning lights with audible alarms, high beam, turn signal, low fuel, parking brake, and ice warning indicators; seat belt reminder; rocker switches with long-life LED indicators; multi-function turn stalk with flash-to-pass feature (night	0	0

Price Level: January 1, 2019

Deal: LINS PX7 Disc

Printed On: 6/10/2019 12:39:41 PM

Date: June 10, 2019

Quote Number: QUO-499527-W0P3B2



Sales Code	Std/Opt	Description	\$ List	Weight
		mode flashes headlights and marker lights; day mode flashes headlights only), intermittent windshield wiper and headlamp beam control. Hydraulic braked trucks do not include air pressure gauges.		
8111110	S	Headlights Composite Fender Mounted Integral park, turn, and side marker	0	0
8120980	S	(5) Marker Lights, Aero LED	0	0
8133470	O	Switch & Wiring For F/O Beacon/Strobe 10' Coiled wire back of cab / back of sleeper at rear sill	56	2
8133960	O	Daytime Running Lights Required on all Canadian vehicles	60	0
8140120	S	Incandescent Square Stop/Turn/Tail/Backup Left-hand / right-hand square end of frame or dropped a-brace	0	0
8152530	O	(2) Load Lights, Bracket Mounted Inboard Loc K DayCab	172	6
8153100	O	(1) F/O Load Light, Switch, 10' Wire Coil Under / in cab / sleeper baggage compartment	19	2

Paint

8500710	O	Standard Paint Color Selection	-200	0
8530770	S	(1) Color Axalta Two Stage - Cab/Hood Base Coat/Clear Coat N85020 A - L0006EY WHITE N85500 CAB ROOF L0006EY WHITE N85300 FENDER L0006EY WHITE N85200 FRAME L0001EA BLACK N85400 HOOD TOP L0006EY WHITE	0	0

Shipping Destination

8999990	O	Shipping Destination Other Than Dealer (Specify by narrative)	0	0
---------	---	---	---	---

Options Not Subject To Discount

9400091	S	Peterbilt Class 7 Standard Coverage 1 year/Unlimited Miles/km	0	0
9400093	O	PACCAR PX-7 Standard Coverage 3 years/Unlimited Miles/Unlimited hrs	0	0
9408931	O	PDI At Excellence Peterbilt Location	230	0
9408936	O	Frame Layout Identical to Previous Chassis <i>Narr 632012</i>	475	0

Miscellaneous

9409800	O	2017 EPA Emissions Engine Warranty Only	0	0
---------	---	---	---	---

Price Level: January 1, 2019

Deal: LINS PX7 Disc

Printed On: 6/10/2019 12:39:41 PM

Date: June 10, 2019

Quote Number: QUO-499527-W0P3B2



Sales Code	Std/ Opt	Description	\$ List	Weight
9409869	O	Presentation Created With SmartSpec	0	0

Promotions

Order Comments



Total List Price (W/O Freight & Warranty & Surcharges)	\$117,018
Marketing and Service Support Fee	\$375
Prepaid Freight	\$2,450
Total Surcharge/Options Not Subject To Discount	\$705
Total Weight	10,318

Prices and Specifications Subject to Change Without Notice.

Unpublished options may require review/approval.
Dimensional and performance data for unpublished options may vary from that displayed in CRM.

PRICING DISCLAIMER

While we make every effort to maintain the web site to preserve pricing accuracy, prices are subject to change without notice. Although the information in this price list is presented in good faith and believed to be correct at the time of printing, we make no representations or warranties as to the completeness or accuracy of this information. We reserve the right to change, delete or otherwise modify the pricing information which is represented herein without any prior notice. We carefully check pricing specifications, but occasionally errors can occur, therefore we reserve the right to change such prices without notice. We disclaim all liability for any errors or omissions in the materials. In no event will we be responsible for any damages of any nature whatsoever from the reliance upon information from these materials. Please check your order prebills to confirm your pricing information