

Prepared for:
 Scott
 Swensen
 LINS PROPANE TRUCKS CORP
 2281 CEDAR ST
 DIGHTON, MA 02715
 Phone: 800-252-5467

S P E C I F I C A T I O N P R O P O S A L

Description	Weight Front	Weight Rear
Price Level		
M2 PRL-27M (EFF:MY24 ORDERS)		
Data Version		
SPECPRO21 DATA RELEASE VER 024		
Vehicle Configuration		
M2 106 PLUS CONVENTIONAL CHASSIS	5,709	3,450
2024 MODEL YEAR SPECIFIED		
SET BACK AXLE - TRUCK		
STRAIGHT TRUCK PROVISION, NON-TOWING		
LH PRIMARY STEERING LOCATION		
General Service		
TRUCK CONFIGURATION		
DOMICILED, USA 50 STATES (INCLUDING CALIFORNIA AND CARB OPT-IN STATES)		
PICKUP AND DELIVERY/SHORT HAUL SERVICE		
PETROLEUM BUSINESS SEGMENT		
LIQUID BULK COMMODITY		
TERRAIN/DUTY: 100% (ALL) OF THE TIME, IN TRANSIT, IS SPENT ON PAVED ROADS		
MAXIMUM 8% EXPECTED GRADE		
SMOOTH CONCRETE OR ASPHALT PAVEMENT - MOST SEVERE IN-TRANSIT (BETWEEN SITES) ROAD SURFACE		
MEDIUM TRUCK WARRANTY		
EXPECTED FRONT AXLE(S) LOAD : 10000.0 lbs		
EXPECTED REAR DRIVE AXLE(S) LOAD : 23000.0 lbs		
EXPECTED GROSS VEHICLE WEIGHT CAPACITY : 33000.0 lbs		



Prepared for:
 Scott
 Swensen
 LINS PROPANE TRUCKS CORP
 2281 CEDAR ST
 DIGHTON, MA 02715
 Phone: 800-252-5467

Description	Weight Front	Weight Rear
POSITIVE AND NEGATIVE POSTS FOR JUMPSTART LOCATED ON FRAME NEXT TO STARTER	2	
PROGRESSIVE LOW VOLTAGE DISCONNECT AT 12.3 VOLTS FOR DESIGNATED CIRCUITS		
CUMMINS TURBOCHARGED 18.7 CFM AIR COMPRESSOR WITH INTERNAL SAFETY VALVE		
STANDARD MECHANICAL AIR COMPRESSOR GOVERNOR		
AIR COMPRESSOR DISCHARGE LINE		
ELECTRONIC ENGINE INTEGRAL SHUTDOWN PROTECTION SYSTEM		
CUMMINS ENGINE INTEGRAL BRAKE WITH VARIABLE GEOMETRY TURBO ON/OFF	20	
RH OUTBOARD UNDER STEP MOUNTED HORIZONTAL AFTERTREATMENT SYSTEM ASSEMBLY WITH RH B-PILLAR MOUNTED VERTICAL TAILPIPE	30	25
ENGINE AFTERTREATMENT DEVICE, AUTOMATIC OVER THE ROAD REGENERATION AND VIRTUAL REGENERATION REQUEST SWITCH IN CLUSTER		
11 FOOT 06 INCH (138 INCH+0/-5.9 INCH) EXHAUST SYSTEM HEIGHT		
STANDARD CURVE BRIGHT UPPER STACK(S)		
RH CURVED VERTICAL TAILPIPE B-PILLAR MOUNTED ROUTED FROM STEP		
13 GALLON DIESEL EXHAUST FLUID TANK	35	10
100 PERCENT DIESEL EXHAUST FLUID FILL		
POLISHED ALUMINUM DIAMOND PLATE DIESEL EXHAUST FLUID TANK COVER	15	5
LH MEDIUM DUTY STANDARD DIESEL EXHAUST FLUID TANK LOCATION		
STANDARD DIESEL EXHAUST FLUID PUMP MOUNTING		
STANDARD DIESEL EXHAUST FLUID TANK CAP		
STAINLESS STEEL AFTERTREATMENT DEVICE/MUFFLER/TAILOPIPE SHIELD		
HIGH SPEED AIR POWERED ON/OFF ENGINE FAN CLUTCH		
AUTOMATIC FAN CONTROL WITHOUT DASH SWITCH, NON ENGINE MOUNTED		
CUMMINS SPIN ON FUEL FILTER		
COMBINATION FULL FLOW/BYPASS OIL FILTER		
1100 SQUARE INCH ALUMINUM RADIATOR	70	



Prepared for:
 Scott
 Swensen
 LINS PROPANE TRUCKS CORP
 2281 CEDAR ST
 DIGHTON, MA 02715
 Phone: 800-252-5467

Description	Weight Front	Weight Rear
ANTIFREEZE TO -34F, OAT (NITRITE AND SILICATE FREE) EXTENDED LIFE COOLANT		
GATES BLUE STRIPE COOLANT HOSES OR EQUIVALENT		
CONSTANT TENSION HOSE CLAMPS FOR COOLANT HOSES		
RADIATOR DRAIN VALVE		
LOWER RADIATOR GUARD		
PHILLIPS-TEMRO 1000 WATT/115 VOLT BLOCK HEATER	4	
CHROME ENGINE HEATER RECEPTACLE MOUNTED UNDER LH DOOR		
ALUMINUM FLYWHEEL HOUSING		
ELECTRIC GRID AIR INTAKE WARMER		
DELCO 12V 38MT HD STARTER WITH INTEGRATED MAGNETIC SWITCH		

Transmission

ALLISON 3000 RDS AUTOMATIC TRANSMISSION WITH PTO PROVISION	200	60
------------------------------------------------------------	-----	----

Transmission Equipment

ALLISON VOCATIONAL PACKAGE 223 - AVAILABLE ON 3000/4000 PRODUCT FAMILIES WITH VOCATIONAL MODELS RDS, HS, MH AND TRV

ALLISON VOCATIONAL RATING FOR ON/OFF HIGHWAY APPLICATIONS AVAILABLE WITH ALL PRODUCT FAMILIES

PRIMARY MODE GEARS, LOWEST GEAR 1, START GEAR 1, HIGHEST GEAR 6, AVAILABLE FOR 3000/4000 PRODUCT FAMILIES ONLY

SECONDARY MODE GEARS, LOWEST GEAR 1, START GEAR 1, HIGHEST GEAR 6, AVAILABLE FOR 3000/4000 PRODUCT FAMILIES ONLY

PRIMARY SHIFT SCHEDULE RECOMMENDED BY DTNA AND ALLISON, THIS DEFINED BY ENGINE AND VOCATIONAL USAGE

SECONDARY SHIFT SCHEDULE RECOMMENDED BY DTNA AND ALLISON, THIS DEFINED BY ENGINE AND VOCATIONAL USAGE

PRIMARY SHIFT SPEED RECOMMENDED BY DTNA AND ALLISON, THIS DEFINED BY ENGINE AND VOCATIONAL USAGE

SECONDARY SHIFT SPEED RECOMMENDED BY DTNA AND ALLISON, THIS DEFINED BY ENGINE AND VOCATIONAL USAGE

Prepared for:
 Scott
 Swensen
 LINS PROPANE TRUCKS CORP
 2281 CEDAR ST
 DIGHTON, MA 02715
 Phone: 800-252-5467

Description	Weight Front	Weight Rear
ENGINE BRAKE RANGE PRESELECT RECOMMENDED BY DTNA AND ALLISON, THIS DEFINED BY ENGINE AND VOCATIONAL USAGE		
ENGINE BRAKE RANGE ALTERNATE PRESELECT RECOMMENDED BY DTNA AND ALLISON, THIS DEFINED BY ENGINE AND VOCATIONAL USAGE		
FUEL SENSE 2.0 DISABLED - PERFORMANCE - TABLE BASED		
DRIVER SWITCH INPUT - DEFAULT - NO SWITCHES		
DIRECTION CHANGE ENABLED WITH MULTIPLEXED SERVICE BRAKES - ALLISON 5TH GEN TRANSMISSIONS		
QUICKFIT BODY LIGHTING CONNECTOR UNDER CAB, WITH BLUNTCUTS		
ELECTRONIC TRANSMISSION WIRING TO CUSTOMER INTERFACE CONNECTOR		
(2) CUSTOMER INSTALLED CHELSEA 280 SERIES PTO'S		
PTO MOUNTING, LH AND RH SIDES OF MAIN TRANSMISSION		
MAGNETIC PLUGS, ENGINE DRAIN, TRANSMISSION DRAIN, AXLE(S) FILL AND DRAIN		
PUSH BUTTON ELECTRONIC SHIFT CONTROL, DASH MOUNTED		
TRANSMISSION PROGNOSTICS - ENABLED 2013		
WATER TO OIL TRANSMISSION COOLER, IN RADIATOR END TANK		
TRANSMISSION OIL CHECK AND FILL WITH ELECTRONIC OIL LEVEL CHECK		
SYNTHETIC TRANSMISSION FLUID (TES-295 COMPLIANT)		

Front Axle and Equipment

DETROIT DA-F-10.0-3 10,000# FF1 71.5 KPI/3.74 DROP SINGLE FRONT AXLE		
MERITOR 15X5 Q+ CAST SPIDER CAM FRONT BRAKES, DOUBLE ANCHOR, FABRICATED SHOES		
NON-ASBESTOS FRONT BRAKE LINING		
CAST IRON OUTBOARD FRONT BRAKE DRUMS		
FRONT BRAKE DUST SHIELDS	5	
FRONT OIL SEALS		

Prepared for:
 Scott
 Swensen
 LINS PROPANE TRUCKS CORP
 2281 CEDAR ST
 DIGHTON, MA 02715
 Phone: 800-252-5467

Description	Weight Front	Weight Rear
VENTED FRONT HUB CAPS WITH WINDOW, CENTER AND SIDE PLUGS - OIL		
STANDARD SPINDLE NUTS FOR ALL AXLES		
MERITOR AUTOMATIC FRONT SLACK ADJUSTERS		
TRW THP-60 POWER STEERING		
POWER STEERING PUMP		
2 QUART SEE THROUGH POWER STEERING RESERVOIR		
CURRENT AVAILABLE SYNTHETIC 75W-90 FRONT AXLE LUBE		
Front Suspension		
12,000# DUAL TAPERLEAF FRONT SUSPENSION	42	
MAINTENANCE FREE RUBBER BUSHINGS - FRONT SUSPENSION		
FRONT SHOCK ABSORBERS		
Rear Axle and Equipment		
DETROIT DA-RS-23.0-4 23,000# R-SERIES SINGLE REAR AXLE		30
5.88 REAR AXLE RATIO		
IRON REAR AXLE CARRIER WITH STANDARD AXLE HOUSING		
MXL 17T MERITOR EXTENDED LUBE MAIN DRIVELINE WITH HALF ROUND YOKES	20	20
DRIVELINE GUARD	25	25
DRIVER CONTROLLED TRACTION DIFFERENTIAL - SINGLE REAR AXLE		20
(1) DRIVER CONTROLLED DIFFERENTIAL LOCK REAR VALVE FOR SINGLE DRIVE AXLE		
INDICATOR LIGHT FOR EACH DIFFERENTIAL LOCKOUT SWITCH, ENGAGE <5 MPH, DISENGAGE >25 MPH		
MERITOR 16.5X7 Q+ CAST SPIDER CAM REAR BRAKES, DOUBLE ANCHOR, FABRICATED SHOES		
NON-ASBESTOS REAR BRAKE LINING		
BRAKE CAMS AND CHAMBERS ON FORWARD SIDE OF DRIVE AXLE(S)		
CAST IRON OUTBOARD REAR BRAKE DRUMS		
REAR BRAKE DUST SHIELDS		5
REAR OIL SEALS		
WABCO TRISTOP D LONGSTROKE 1-DRIVE AXLE SPRING PARKING CHAMBERS		



Prepared for:
 Scott
 Swensen
 LINS PROPANE TRUCKS CORP
 2281 CEDAR ST
 DIGHTON, MA 02715
 Phone: 800-252-5467

Description	Weight Front	Weight Rear
MERITOR AUTOMATIC REAR SLACK ADJUSTERS		
CURRENT AVAILABLE SYNTHETIC 75W-90 REAR AXLE LUBE		
Rear Suspension		
23,000# 52 INCH VARIABLE RATE MULTI-LEAF SPRING REAR SUSPENSION WITH LEAF SPRING HELPER		110
SPRING SUSPENSION - NO AXLE SPACERS		
STANDARD U-BOLT PAD WITH U-BOLTS EXTENDED 1.00" LONGER THAN STANDARD		
Brake System		
AIR BRAKE PACKAGE		
WABCO 4S/4M ABS WITH TRACTION CONTROL		
REINFORCED NYLON, FABRIC BRAID AND WIRE BRAID CHASSIS AIR LINES		
FIBER BRAID PARKING BRAKE HOSE		
STANDARD BRAKE SYSTEM VALVES		
STANDARD AIR SYSTEM PRESSURE PROTECTION SYSTEM		
STD U.S. FRONT BRAKE VALVE		
RELAY VALVE WITH 5-8 PSI CRACK PRESSURE, NO REAR PROPORTIONING VALVE		
BW AD-9 BRAKE LINE AIR DRYER WITH HEATER	20	
AIR DRYER MOUNTED UNDER HOOD		
STEEL AIR BRAKE RESERVOIRS; CUSTOMER ACCEPTS TANKS MOUNTED PERPENDICULAR TO RAIL	10	10
PULL CABLE ON WET TANK, PETCOCK DRAIN VALVES ON ALL OTHER AIR TANKS		
Wheelbase & Frame		
5175MM (204 INCH) WHEELBASE		
11/32X3-1/2X10-15/16 INCH STEEL FRAME (8.73MMX277.8MM/0.344X10.94 INCH) 120KSI	170	110
2025MM (80 INCH) REAR FRAME OVERHANG		
FRAME OVERHANG RANGE: 71 INCH TO 80 INCH	-20	90
CALC'D BACK OF CAB TO REAR SUSP C/L (CA) : 138.19 in		
CALCULATED EFFECTIVE BACK OF CAB TO REAR SUSPENSION C/L (CA) : 135.19 in		
CALC'D FRAME LENGTH - OVERALL : 312.83 in		



Prepared for:
 Scott
 Swensen
 LINS PROPANE TRUCKS CORP
 2281 CEDAR ST
 DIGHTON, MA 02715
 Phone: 800-252-5467

Description	Weight Front	Weight Rear
CALCULATED FRAME SPACE LH SIDE : 70.4 in		
CALCULATED FRAME SPACE RH SIDE : 85.79 in		
SQUARE END OF FRAME		
FRONT CLOSING CROSSMEMBER		
STANDARD WEIGHT ENGINE CROSSMEMBER		
STANDARD CROSSMEMBER BACK OF TRANSMISSION		
STANDARD MIDSHIP #1 CROSSMEMBER(S)		
STANDARD REARMOST CROSSMEMBER		
STANDARD SUSPENSION CROSSMEMBER		
Chassis Equipment		
THREE-PIECE 14 INCH CHROMED STEEL BUMPER WITH COLLAPSIBLE ENDS	30	
FRONT TOW HOOKS - FRAME MOUNTED BUMPER MOUNTING FOR SINGLE LICENSE PLATE	15	
FENDER AND FRONT OF HOOD MOUNTED FRONT MUDFLAPS		
GRADE 8 THREADED HEX HEADED FRAME FASTENERS		
Fuel Tanks		
50 GALLON/189 LITER RECTANGULAR ALUMINUM FUEL TANK - LH RECTANGULAR FUEL TANK(S) POLISHING OF FUEL/HYDRAULIC TANK(S) WITH PAINTED BANDS FUEL TANK(S) FORWARD POLISHED STAINLESS STEEL STEP FINISH FUEL TANK CAP(S)	20	
DETROIT FUEL/WATER SEPARATOR WITH WATER IN FUEL SENSOR, HAND PRIMER AND 12 VOLT PREHEATER"	-5	
EQUIFLO INBOARD FUEL SYSTEM HIGH TEMPERATURE REINFORCED NYLON FUEL LINE		
Tires		
BRIDGESTONE R213 ECOPIA 11R22.5 14 PLY RADIAL FRONT TIRES	6	
BRIDGESTONE M726ELA 11R22.5 14 PLY RADIAL REAR TIRES		76
Hubs		



Prepared for:
 Scott
 Swensen
 LINS PROPANE TRUCKS CORP
 2281 CEDAR ST
 DIGHTON, MA 02715
 Phone: 800-252-5467

Description	Weight Front	Weight Rear
CONMET PRESET PLUS PREMIUM IRON FRONT HUBS		
CONMET PRESET PLUS PREMIUM IRON REAR HUBS		
Wheels		
ALCOA ULA18X 22.5X8.25 10-HUB PILOT 5.81 INSET ALUMINUM DISC FRONT WHEELS	-62	
ALCOA ULA18X 22.5X8.25 10-HUB PILOT ALUMINUM DISC REAR WHEELS		-124
POLISHED FRONT WHEELS; OUTSIDE ONLY		
POLISHED REAR WHEELS; OUTSIDE OF OUTER WHEELS ONLY		
FRONT WHEEL MOUNTING NUTS		
REAR WHEEL MOUNTING NUTS		
NYLON WHEEL GUARDS BETWEEN REAR DUAL WHEELS ONLY		
Cab Exterior		
106 INCH BBC FLAT ROOF ALUMINUM CONVENTIONAL CAB		
AIR CAB MOUNTING		
NONREMOVABLE BUGSCREEN MOUNTED BEHIND GRILLE		
LH AND RH GRAB HANDLES		
HOOD MOUNTED CHROMED PLASTIC GRILLE		
CHROME HOOD MOUNTED AIR INTAKE GRILLE		
FIBERGLASS HOOD		
DUAL 26 INCH RECTANGULAR POLISHED ALUMINUM AIR HORNS ROOF MOUNTED	8	
DUAL ELECTRIC HORNS		
DUAL HORN SHIELDS		
REAR LICENSE PLATE MOUNT END OF FRAME SWITCH, INDICATOR LIGHT AND WIRING FOR (2) CUSTOMER FURNISHED BEACONS		
INTEGRAL HEADLIGHT/MARKER ASSEMBLY WITH CHROME BEZEL		
LED AERODYNAMIC MARKER LIGHTS		
DAYTIME RUNNING LIGHTS		
OMIT STOP/TAIL/BACKUP LIGHTS AND PROVIDE WIRING WITH SEPARATE STOP/TURN WIRES TO 4 FEET BEYOND END OF FRAME		-5
STANDARD FRONT TURN SIGNAL LAMPS		



Prepared for:
 Scott
 Swensen
 LINS PROPANE TRUCKS CORP
 2281 CEDAR ST
 DIGHTON, MA 02715
 Phone: 800-252-5467

Description	Weight Front	Weight Rear
SWITCH, INDICATOR LIGHT AND APPROXIMATELY 10 FEET OF WIRE ON CHASSIS RH BACK OF CAB FOR CUSTOMER FURNISHED UTILITY LIGHT(S)		
DUAL WEST COAST BRIGHT FINISH HEATED MIRRORS WITH LH AND RH REMOTE		
DOOR MOUNTED MIRRORS		
102 INCH EQUIPMENT WIDTH		
LH AND RH 8 INCH BRIGHT FINISH CONVEX MIRRORS MOUNTED UNDER PRIMARY MIRRORS		
RH DOWN VIEW MIRROR		
STANDARD SIDE/REAR REFLECTORS		
RH AFTERTREATMENT SYSTEM CAB ACCESS WITH POLISHED DIAMOND PLATE COVER		
PARK BRAKE REMINDER WARNING SYSTEM		
COMPOSITE EXTERIOR SUN VISOR	10	
63X14 INCH TINTED REAR WINDOW		
TINTED DOOR GLASS LH AND RH WITH TINTED NON-OPERATING WING WINDOWS		
RH AND LH ELECTRIC POWERED WINDOWS	4	
LOWER RH DOOR WINDOW WITH FRESNEL LENS	7	
1-PIECE SOLAR GREEN GLASS WINDSHIELD		
2 GALLON WINDSHIELD WASHER RESERVOIR WITHOUT FLUID LEVEL INDICATOR, FRAME MOUNTED		
Cab Interior		
ELITE TRIM PACKAGE		
MIST CLOTH & CARBON VINYL INTERIOR "ELITE"		
CARBON WITH PREMIUM WOOD ACCENT (ELITE)		
MOLDED PLASTIC DOOR PANEL		
MOLDED PLASTIC DOOR PANEL		
BLACK MATS WITH SINGLE INSULATION		
(1)DASH MOUNTED 12V POWER OUTLET		
(1)DASH MOUNTED DUAL 2.1 AMP USB-C CHARGER		
FORWARD ROOF MOUNTED CONSOLE		
CENTER STORAGE CONSOLE MOUNTED ON BACKWALL	20	
LH AND RH KICKPLATES		

Prepared for:
 Scott
 Swensen
 LINS PROPANE TRUCKS CORP
 2281 CEDAR ST
 DIGHTON, MA 02715
 Phone: 800-252-5467

Description	Weight Front	Weight Rear
DIGITAL ALARM CLOCK IN DRIVER DISPLAY		
(2) CUP HOLDERS LH AND RH DASH		
M2/SD DASH		
5 LB. FIRE EXTINGUISHER	10	
FIRST AID KIT	2	
HEATER, DEFROSTER AND AIR CONDITIONER		
STANDARD HVAC DUCTING		
MAIN HVAC CONTROLS WITH RECIRCULATION SWITCH		
STANDARD HEATER PLUMBING		
VALEO HEAVY DUTY A/C REFRIGERANT COMPRESSOR		
BINARY CONTROL, R-134A		
STANDARD INSULATION		
SOLID-STATE CIRCUIT PROTECTION AND FUSES		
12V NEGATIVE GROUND ELECTRICAL SYSTEM		
PREMIUM LED CAB LIGHTING		
DOOR LOCKS AND IGNITION SWITCH KEYED THE SAME		
KEY QUANTITY OF 2		
LH AND RH ELECTRIC DOOR LOCKS		
TRIANGULAR REFLECTORS WITHOUT FLARES	10	
ELITE ISRINGHAUSEN HIGH BACK AIR SUSPENSION DRIVERS SEAT W/2 AIR LUMBAR, INTEGRATED CUSHION EXTENSION, TILT, ADJUSTABLE SHOCK, HEAT	70	
BASIC ISRI HIGH BACK NON SUSPENSION PASSENGER SEAT		
DUAL DRIVER AND PASSENGER SEAT ARMRESTS	8	
LH AND RH INTEGRAL DOOR PANEL ARMRESTS		
BLACK MORDURA CLOTH DRIVER SEAT COVER		
BLACK MORDURA CLOTH PASSENGER SEAT COVER		
BLACK SEAT BELTS		
ADJUSTABLE TILT AND TELESCOPING STEERING COLUMN	10	
4-SPOKE 18 INCH (450MM) LEATHER WRAPPED STEERING WHEEL WITH CHROME SWITCH BEZELS		
DRIVER AND PASSENGER INTERIOR SUN VISORS		



Prepared for:
 Scott
 Swensen
 LINS PROPANE TRUCKS CORP
 2281 CEDAR ST
 DIGHTON, MA 02715
 Phone: 800-252-5467

Description	Weight Front	Weight Rear
Instruments & Controls		
DIGITAL PANEL LAMP DIMMER SWITCH IN DRIVER DISPLAY		
ELECTRONIC ACCELERATOR CONTROL		
NO INSTRUMENT PANEL-DRIVER		
INTEGRATED UPPER & LOWER STORAGE PANELS		
(4) SWITCH CUTOUTS AND BLANKS IN CENTER PANEL		
ENGINE REMOTE INTERFACE WITH PARK BRAKE INTERLOCK		
BRIGHT ARGENT FINISH GAUGE BEZELS		
LOW AIR PRESSURE INDICATOR LIGHT AND AUDIBLE ALARM		
DUAL NEEDLE PRIMARY AND SECONDARY AIR PRESSURE GAUGE		
INTAKE MOUNTED AIR RESTRICTION INDICATOR WITHOUT GRADUATIONS		
ELECTRONIC CRUISE CONTROL WITH CONTROLS ON STEERING WHEEL SPOKES		
KEY OPERATED IGNITION SWITCH AND INTEGRAL START POSITION; 4 POSITION OFF/RUN/START/ACCESSORY		
PREMIUM INSTRUMENT CLUSTER WITH 5.0 INCH TFT COLOR DISPLAY		
HEAVY DUTY ONBOARD DIAGNOSTICS INTERFACE CONNECTOR LOCATED BELOW LH DASH		
2 INCH ELECTRIC FUEL GAUGE		
ENGINE REMOTE INTERFACE WITH MULTIPLE SET SPEEDS		
QUICKFIT POWERTRAIN INTERFACE CONNECTOR UNDER CAB WITH BLUNTCUTS		
ELECTRICAL ENGINE COOLANT TEMPERATURE GAUGE		
2 INCH TRANSMISSION OIL TEMPERATURE GAUGE		
ELECTRONIC OUTSIDE TEMPERATURE SENSOR DISPLAY IN DRIVER MESSAGE CENTER		
ENGINE AND TRIP HOUR METERS INTEGRAL WITHIN DRIVER DISPLAY		
ELECTRIC ENGINE OIL PRESSURE GAUGE		
NO OVERHEAD INSTRUMENT PANEL		



Prepared for:
 Scott
 Swensen
 LINS PROPANE TRUCKS CORP
 2281 CEDAR ST
 DIGHTON, MA 02715
 Phone: 800-252-5467

Description	Weight Front	Weight Rear
AM/FM/WB WORLD TUNER RADIO WITH BLUETOOTH, USB AND AUXILIARY INPUTS, J1939	10	
DASH MOUNTED RADIO		
(2) RADIO SPEAKERS IN CAB		
AM/FM ANTENNA MOUNTED ON FORWARD LH ROOF		
STANDARD RADIO WIRING WITH STEERING WHEEL CONTROLS		
ELECTRONIC MPH SPEEDOMETER WITH SECONDARY KPH SCALE, WITHOUT ODOMETER		
STANDARD VEHICLE SPEED SENSOR		
ELECTRONIC 3000 RPM TACHOMETER		
DETROIT CONNECT PLATFORM HARDWARE		
TMC RP1226 ACCESSORY CONNECTOR LOCATED BEHIND PASSENGER SIDE REMOVEABLE DASH PANEL		
IGNITION SWITCH CONTROLLED ENGINE STOP		
ONE EXTRA HARDWIRED SWITCH IN DASH, ROUTE TO UNDER CAB, CAPPED		
HARDWIRE SWITCH #1, ON/OFF LATCHING, 10 AMPS BATTERY POWER		
(1) OVERHEAD MOUNTED LANYARD CONTROL FOR DRIVER AIR HORN		
DIGITAL VOLTAGE DISPLAY INTEGRAL WITH DRIVER DISPLAY		
SINGLE ELECTRIC WINDSHIELD WIPER MOTOR WITH DELAY AND ARCTIC TYPE BLADES		
ROTARY HEADLAMP SWITCH, MARKER LIGHTS/HEADLIGHTS SWITCH WITH PULL OUT FOR OPTIONAL FOG/ROAD LAMPS		
ONE VALVE PARKING BRAKE SYSTEM WITH DASH VALVE CONTROL AUTONEUTRAL AND WARNING INDICATOR		
SELF CANCELING TURN SIGNAL SWITCH WITH DIMMER, HEADLAMP FLASH, WASH/WIPE/INTERMITTENT		
INTEGRAL ELECTRONIC TURN SIGNAL FLASHER WITH 40 AMP (20 AMP PER SIDE) TRAILER LAMP CAPACITY		

Design

PAINT: ONE SOLID COLOR

Color



Prepared for:
 Scott
 Swensen
 LINS PROPANE TRUCKS CORP
 2281 CEDAR ST
 DIGHTON, MA 02715
 Phone: 800-252-5467

Description	Weight Front	Weight Rear
CAB COLOR A: L0006EY WHITE ELITE EY BLACK, HIGH SOLIDS POLYURETHANE CHASSIS PAINT SUNVISOR PAINTED SAME AS CAB COLOR A STANDARD E COAT/UNDERCOATING		

Certification / Compliance

U.S. FMVSS CERTIFICATION, EXCEPT SALES
 CABS AND GLIDER KITS

Secondary Factory Options

CORPORATE PDI CENTER IN-SERVICE ONLY

TOTAL VEHICLE SUMMARY

Weight Summary

	Weight Front	Weight Rear	Total Weight
Factory Weight ⁺	7192 lbs	3947 lbs	11139 lbs
Total Weight ⁺	7192 lbs	3947 lbs	11139 lbs

Extended Warranty

TOWING: TOWING: 1 YEAR/UNLIMITED MILES/KM EXTENDED
 TOWING COVERAGE \$750 CAP FEX APPLIES

(+) Weights shown are estimates only.

If weight is critical, contact Customer Application Engineering.

(***) All cost increases for major components (Engines, Transmissions, Axles, Front and Rear Tires) and government mandated requirements, tariffs, and raw material surcharges will be passed through and added to factory invoices.



Prepared for:
Scott
Swensen
LINS PROPANE TRUCKS CORP
2281 CEDAR ST
DIGHTON, MA 02715
Phone: 800-252-5467

