



**KENWORTH OF PENNSYLVANIA - CARLISLE (M420)**  
**198 KOST ROAD**  
**CARLISLE, Pennsylvania 17013**

**LINS PROPANE TRUCKS**  
**2281 CEDAR ST**  
**DIGHTON, Massachusetts 02715**  
**United States of America**

**Matthew Puliti**  
**Cell Phone:**  
**Office Phone: 717-766-8000**  
**Email: mpuliti@kwofpa.com**

**ANDY JOHNSON**  
**Cell Phone: 508-400-6083**  
**Office Phone: 1-800-252-5467**  
**Email: andy@linspropanetrucks.com**

## Vehicle Summary

	<b>Unit</b>	<b>Chassis</b>	
Model:	T380 Series Conventional	Fr Axle Load (lbs):	10000
Type:	FULL TRUCK	Rr Axle Load (lbs):	23000
Description 1:	T380 Chassis	G.V.W.R. (lbs):	33000
Description 2:	T380 Propane Chassis Updated	G.C.W. (lbs):	33000
<b>Application</b>		Road Conditions:	
Intended Serv.:	Local Pickup & Delivery: Vehicles which	Class A (Highway)	90
Commodity:	Crude oil.	Class B (Hwy/Mtn)	10
		Class C (Off-Hwy)	0
		Class D (Off-Road)	0
	<b>Body</b>	Maximum Grade:	6
Type:	Tank	Wheelbase (in):	205
Length (ft):	12	Overhang (in):	95
Height (ft):	12	Fr Axle to BOC (in):	67.5
Max Laden Weight (lbs):	17500		
		Cab to Axle (in):	137.5
		Cab to EOF (in):	232.5
		Overall Comb. Length (in):	340
No. of Trailer Axles:	0		
Type:		<b>Special Req.</b>	
Length (ft):	0	U.S. Domestic Registry, 50-state.	
Height (ft):	0		
Kingpin Inset (in):	0		
Corner Radius (in):	0		
	<b>Restrictions</b>		
Length (ft):	75		
Width (in):	102		
Height (ft):	13.5		

**Approved by:** \_\_\_\_\_

**Date:** \_\_\_\_\_

**Note: All sales are F.O.B. designated plant of manufacture.**

Sales Code	Std/Opt	Description	Weight
<b>Model</b>			
0000380	S	<b>T380 Series Conventional</b>	<b>9,930</b>
0070086	S	<b>T380 Aero Hood</b>	<b>0</b>
0080101	O	<b>CARB Low NOX Omnibus Registration Guidelines</b> Dealer/Customer acknowledges that this vehicle is NOT intended for registration or domicile/primary use in the State of California.	<b>0</b>
0080314	O	<b>EPA Clean Idle Label - PACCAR PX Engines</b>	<b>0</b>
0090143	O	<b>T380 Automatic</b>	<b>0</b>
0098421	O	<b>State of Registry: Massachusetts</b>	<b>0</b>
<b>Engine &amp; Equipment</b>			
0130126	O	<b>PACCAR PX-7 325 325@2400 750@1600, 2024</b> With Turbo Exhaust Brake (VGT Brake) N09420 C333 0.....Reserve Speed Limit Offset ( N09380 C334 0.....Maximum Cycle Distance (C334 N09360 C400 252...Reserve Speed Function Reset N09200 C399 100...Standard Maximum Speed Limit N09400 C401 10....Maximum Active Distance (C40 N09220 C402 0.....Expiration Distance (C402) N09540 C395 0.....Expiration Distance (C395) N09260 C121 70....Max Vehicle Speed in Top Gea N09440 C234 NO....Engine Protection Shtdwn N09460 C231 NO....Gear Down Protection N09580 C133 1.....Idle Shtdwn Time N09680 C233 NO....Idle Shtdwn Override N09480 C132 1400..Max PTO Speed N09300 C128 70....Max Cruise Control Speed N09500 C239 NO....Cruise Control Auto Resume N09520 C238 NO....Auto Engine Brake in Cruise N09780 C190 80....High Ambient Temperature Thr N09740 C188 40....Low Ambient Temperature Thre N09760 C189 60....Intermediate Ambient Tempera N09720 C382 YES...Enable Hot Ambient Automatic N09600 C396 YES...Enable Impending Shutdown Wa N09620 C397 60....Timer For Impending Shutdown N09640 C206 35....Engine Load Threshold N09560 C225 NO....Enable Idle Shutdown Park Br	<b>0</b>
1000046	O	<b>EPA Emissions Compliant Engine</b>	<b>0</b>
1000151	S	<b>PremierSpec</b>	<b>0</b>
1000244	O	<b>Gearing Analysis: Balance</b> power/economy blend results.	<b>0</b>
1000256	O	<b>Customer's Typical Operating Spd: 64 MPH</b>	<b>0</b>

Price Level: January 1, 2026

98% Complete

Date: February 24, 2026

Deal: T380 Chassis

Quote Number: QUO-1160190-S9N2L0

Printed On: 2/24/2026 7:50:13 AM

Sales Code	Std/Opt	Description	Weight
1000526		<b>RegistrationYear</b> Year of Registration: 2026	0
1000684	O	<b>Effective VSL Setting NA</b>	0
1000858	O	<b>Engine Idle Shutdown Timer Disabled</b>	0
1000891	O	<b>Eff EIST NA Expiration Miles</b> Use only with MX and Cummins engines	0
1002060	S	<b>Air Compressor: Cummins 18.7 CFM For Cummins And PACCAR PX engines.</b>	0
1041399	S	<b>Air Cleaner: MD Composite Engine Mounted</b>	0
1098003	S	<b>Air Restriction Indicator: Mechanical</b> Mounted on Air Cleaner.	0
1105261	S	<b>Fan Hub: Horton On/Off for PX-7 or B6.7N</b>	0
1121231	S	<b>Cooling Module: 2.1M MD - Aero Hood</b> 1000 Square Inches	0
1160214	O	<b>Bug Screen: Behind Grille</b>	2
1234567	U	<b>No PTO Switch</b> <i>Narr No PTO Switch No PTO Switch Installed Customer remote wires PTO</i>	0
1247263	O	<b>EXH: Single Can 2024 RH Under with RH</b> Side-of-Cab Vertical Tailpipe	0
1290124	O	<b>Tailpipe: 5 in. single 24 in. 45 degree curved.</b>	6
1321102	S	<b>Fuel Filter: PACCAR 2.1M MD for PX-7 or PX-9</b> Fuel/water separator for 2021 and later engines.	0
1321205	O	<b>Run Aid:Fuel Heat</b> *For Fuel Filter	0
1321305	O	<b>Start Aid:12V Heat</b> *For Fuel Filter	1
1500029	O	<b>Kenworth Fuel Cooler</b> Required for Cummins engines with a single fuel tank. Required for PACCAR MX-13 engine with a single fuel tank and stationary use: High RPM, low vehicle speed, sustained for longer than 1 hour. Optional for all other applications.	0
1504006	O	<b>Block Heater: PACCAR 750 watt 120V for PX-7 and B6.7N. 1000 watt for PX-9 and ISL9 Engines.</b>	2
1812163	S	<b>Alternator: PACCAR HDS 160 AMP Brushed</b>	0
1821225	O	<b>Batteries: 2 PACCAR GP31 Threaded Post (1000)</b> 2000 CCA starting.	4
1836107	S	<b>Starter: PACCAR 90P47 12V with PACCAR PX-7</b>	0
1840065	S	<b>12V Low Voltage Disconnect for Battery Protection</b>	0
1840067	O	<b>Battery Disconnect Switch Mounted on Battery Box</b>	0

Sales Code	Std/Opt	Description	Weight
		Provides One (1) Switch	
1901018	S	<b>Remote PTO/Throttle, 12-Pin, 250K, Back of Cab</b> OR Back of Sleeper, J1939, Remote Control Provision	0
<b>Transmission &amp; Clutch</b>			
2011613	O	<b>Transmission: Allison 3000RDS 6-speed, With PTO</b> drive gear. 6th Generation controls. Includes heat exchanger & oil level sensor. Rugged Duty Series for vocational applications. Requires a push button shift control code. Oil temperature gauge is standard on class 8 models. Transynd transmission fluid is standard on all Allison 1000, 2000, 3000 & 4000 series transmissions.	443
2406466	O	<b>Driveline: 2 Dana SPL170SF With 1 Centerbearing</b>	84
2409941	O	<b>One Heavy-Duty One-Piece Aluminum Crossmember</b> This option upgrades an existing crossmember. The cost does not include the centerbearing and bracket. Crossmember location will be in accordance with Kenworth engineering standards, using the major components specified on the DTPO.	0
2410018	O	<b>Torque Converter Included W/ Allison</b> Transmission.	0
2410153	O	<b>Push Button Shifter Controls, Center Console</b> Mounted for Allison Transmission. 2.1m Medium Duty only.	0
2410204	O	<b>Allison Fuel Sense: Delete</b>	0
2410244	O	<b>J1939 Park Brake Auto Neutral</b>	0
2410310	O	<b>Allison Neutral at Stop</b>	0
2429358	O	<b>Rear Transmission Support Springs for</b> transmission PTO applications are required to ensure that engine flywheel housings are not overloaded when transmission PTO's are installed.	0
2429378	O	<b>Customer Installed Transmission PTO in the LH</b> Mounted position (8 o'clock) for Allison 3000 & 4000 transmissions.	0
<b>Front Axle &amp; Equipment</b>			
2531104	O	<b>Hendrickson Steertek Front Axle rated 10k</b> Standard Track 3.32 in. drop.	-13
2621310	S	<b>Front Brakes: 14.6K Bendix ES S-Cam 16.5x5 in.</b>	0
<b>2659047</b>	<b>O</b>	<b>Front Dustshield: for Drum Brakes:</b> All Front Axles.	6
2690002	S	<b>Front Brake Drums: 14.6K 16.5x5 in. cast.</b>	0
2701300	O	<b>Front Hub: Aluminum Hub Pilot 13,200 lbs.</b> 10-Bolt, 11-1/4 in. bolt circle .	0
2741970	S	<b>ConMet PreSet Plus Hub Package; Front Axle.</b>	0

Sales Code	Std/Opt	Description	Weight
2750001	S	<b>Hubcap: Front Vented.</b>	0
2765001	S	<b>Front Auto Slack Adjuster for Drum Brakes.</b>	0
2883002	S	<b>Front Springs: Mono-leaf 12K W/ Shock Absorbers</b> With maintenance-free elastomer spring pin bushings.	0
2895223	S	<b>Single Power Steering Gear: 13.2K for Air Brakes.</b>	0
2900055	O	<b>5 mm Front Suspension Spacer Block</b>	0
<b>Rear Axle &amp; Equipment</b>			
3042160	O	<b>Single Meritor RS23-160 Rear Axle rated at 23K.</b>	169
3200614	O	<b>Rear Axle Ratio - 6.14.</b>	0
3330004	S	<b>Single Rear Brakes 16-1/2x7 in. Bendix ES-</b> extended service S-cam.	0
3392007	S	<b>Single Rear Brake Drums: Cast S-Cam Single</b> For use with 15x8.625", 16.5X7" or 16.5X8.625" brake.	0
3403220	S	<b>Single Rear Hubs: Iron Hub Pilot 26k; 11.25" Bolt</b> circle. Requires "R" series outer ends.	0
3441971	S	<b>ConMet PreSet Plus Hub Package; Single Rear Axle.</b>	0
3465900	O	<b>Rear Slack Adjusters Included W/ Axle or Air</b> disc brakes.	0
3485007	S	<b>Spring Brake: 3030 Long Stroke Single 3 in.</b> travel. For drum brakes. Helps keep brakes in adjustment longer.	0
3490047	O	<b>Dustshields for Drum Brakes: All Rear Axles.</b>	11
3495226	S	<b>Bendix 4S/4M Anti-Lock Brake System.</b>	0
3495561	O	<b>Air Operated Park Brake</b>	0
3511080	O	<b>Meritor Driver Controlled Differential Lock for</b> single rear axle.	0
<b>3646417</b>	<b>U</b>	<b>Rear suspension: single Reyco 79KB multileaf 26K</b>	0
3836315	O	<b>Bolted Rear Suspension Crossmembers for Reyco</b> 79KB. Replaces medium duty standard.	41
<b>Tires &amp; Wheels</b>			
4080047	O	<b>Front Tires: Continental HSR3 11R22.5 16PR</b> Includes pressure sensor.	38
4280057	O	<b>Rear Tires: Continental HDR2+ 11R22.5 14PR</b>	88
4900004	O	<b>Rear Tire Quantity: 4</b>	0
5045306	O	<b>Front Wheel: Alcoa 88067 22.5x8.25 MagnaForce</b>	-51

Sales Code	Std/Opt	Description	Weight
		aluminum alloy, hub-pilot mount. 7400 lb maximum rating. Air disc brake compatible. High polish.	
5245306	O	<b>Rear Wheel: Alcoa 88067 22.5x8.25 MagnaForce</b> aluminum alloy, hub-pilot mount. 7400 lb maximum rating. Air disc brake compatible. High polish.	-102
5859010	O	<b>Single Front Axle: 2 wheels Dura-Bright Mirror</b> Polish Dura-Bright outboard surface of aluminum wheels.	0
5859028	O	<b>Single Rear Axle: Dura-Bright Mirror Polish</b> wide base singles, outboard surface (quantity 2) -1DB.	0
5900004	O	<b>Rear Wheel/Rim Quantity: 4</b>	0

### Frame & Equipment

6054410	O	<b>Frame Rails: 10-5/8 x 3-1/2 x 5/16 in. Steel to</b> 309 in. to 380 in. Truck frame weight is 2.91 lb.-in. per pair of rails. Section modulus is 14.80 cu.in., RBM is 1,776,000 in.-lbs per rail. 120,000 PSI yield. Heat treated. Frame rail availability may be restricted based upon application, axle/suspension capacity, fifth wheel setting, or component/dimensional specifications. The results of the engineering review may result in a change to the requested frame rail. If a change is required, Kenworth Application Engineering will advise the dealer of the appropriate material specification for a substitute rail.	264
6308715	O	<b>Bumper: Aerodynamic Chrome Steel. Requires a bumper setting code.</b>	68
6319040	S	<b>40 in. Bumper Setting. Requires a Bumper Code.</b>	0
6321010	S	<b>Front Tow Loops: Two</b>	0
6404422	S	<b>Battery Box: Steel Parallel Module under W/Step,</b> plastic cover. Use with 2 or 3 batteries. Up to 2 air tanks may be mounted to bottom of box. Batteries will be oriented perpendicular to the frame rail in a single row.	0
6409901	O	<b>Battery Box Location: LH Side.</b>	0
6451125	O	<b>DPF/SCR Box Natural End Plates and Natural cover.</b>	0
6490139	O	<b>Heavy-Duty One-PC Aluminum Intermediate/ Fill-In crossmember.</b>	13
6490434	O	<b>Heavy-Duty 5-Piece Rear Cab Support, Bolted assembly. Huck fastened to frame.</b>	15
6742009	S	<b>Square End-of-Frame W/O Crossmember; Non-Towing.</b>	0

### Fuel Tanks & Equip

7144050	O	<b>50 US Gallon D-Shape Rectangular Aluminum BOC</b> fuel tank, replace.	-22
7722173	O	<b>Large DEF Tank, 15 Gallons.</b>	26
7840015	O	<b>Polish Only One Aluminum Tank.</b>	0
7840038	O	<b>Polished Cover for 1 DEF Tank Any Size.</b>	3

Sales Code	Std/Opt	Description	Weight
7889007	O	<b>Fuel Fill: Center of Tank(s) BOC. Not</b> available on fuel tanks with 3 supports or with full or partial chassis fairings.	0
7889061	O	<b>Polished Stainless Steel Tank Straps for 1 Tank.</b>	0
7889203	O	<b>DEF to Fuel Fill Ratio 2:1 or Greater.</b>	0
7889613	O	<b>DEF Tank Location is RH BOC. For 2.1M Medium-Duty</b>	0
7940050	O	<b>Location: 50 gal fuel tank LH behind cab.</b>	0
<b>Cab &amp; Equipment</b>			
8024311	S	<b>Cab: Stamped Aluminum with Curved Windshield</b> LED markers. Requires separate roof code.	0
8090154	O	<b>Hood: Short Aero w/ Chrome Crown</b>	0
8108011	S	<b>Cab HVAC - Day Cab and 40 in. Sleeper</b> System With Defrost, A/C, and 48,000 BTU/hr Heater. Includes automatic temperature control with one touch defrost operation and dash mounted cab temperature and solar intensity sensors. Pleated fresh air filter and cabin recirculation air filter standard. The Kenworth HVAC system is designed to provide optimal heating and cooling in all operating environments without need for additional insulation. Cab HVAC without sleeper heater AC is available with 40in sleeper.	0
8201047	O	<b>Kenworth Smartwheel: 18 in. Non-Leather With</b> Integrated Radio and Cruise Controls.	0
8201200	S	<b>Adjustable Telescoping Tilt Steering Column.</b>	0
8203060	O	<b>5 Sets of Keys. Replaces Standard 2 Sets of Keys.</b>	0
8205135	O	<b>Information for Customer-Installed PTO Muncie</b> 10-bolt.	0
8208476	O	<b>Three Spare Switches: Wired to Power. BOC Wire</b> termination.	0
8282024	S	<b>Main Instrument Package: 7" Digital Display</b> Cluster. Includes Physical (Analog): Speedometer, Tachometer, Oil Pressure, and Coolant Temp; and Digital: Fuel Level #1, DEF Level, DPF Filter Status, Fuel Economy, Volts Telltale, OAT and Primary Air Pressure, Secondary Air Pressure, and Air Application for air brake trucks.	0
8330591	S	<b>Interior Trim Package: 2.1M MD Gray Foam</b> Backing/Cloth Headliner W/Gray Sunvisor & Seat Color Three Underdash Center Console Cupholders (Two If Allison Transmission Is Selected).	0
8410212	O	<b>Driver Seat: KW Premium Air Seat HB Vinyl w/ Dual</b> Armrests/Susp Cover/Seat Heater	0
8480232	O	<b>Rider Seat: KW Toolbox Seat HB Vinyl w/ Dual</b> Armrests/Record Holder/Occupancy Sensor	0

Sales Code	Std/Opt	Description	Weight
8490161	O	Seat Color: Black Replacing Standard Gray	0
8601432	O	Kenworth Radio DEA710 AM/FM/WB/USB, Bluetooth	0
8698965	O	Speaker Package For Cab: (2) Speakers B-Pillar	0
<b>8700161</b>	<b>O</b>	<b>Footwell Light: Red Lens &amp; Switch</b>	<b>0</b>
8700196	S	Turn Signal: Self-Cancelling	0
8700283	S	LH and RH Trip Ledge Rain Deflectors	0
8700501	O	Metal Int Door Panel Kick Plates	0
8700604	O	TELEMATICS HW (MASS RIGHT TO REPAIR)	0
8800260	O	Long Grabhandle RH Side Mounted to Side-of-Cab exhaust.	2
8800372	O	Grabhandle: LH, Exterior, Side of Cab - Ergonomic Grab Handle Mounted To The Left Hand Exterior Of The Cab For Entry and Exit.	3
8800402	S	Dual Cab Interior Grabhandles: A Pillar Mounted Dash Wrap and B Pillar Mounted Grabhandles	0
8832113	S	Kenworth Daylite Door With Standard LH/RH electric door locks and LH/RH electric window controls.	0
8841642	O	Air Horn: Dual Round 26" LH/RH Roof Incl Air Horn Cover	0
8850139	S	Look-Down, Pass. Door, Black 11x6	0
8850841	O	Mirror Shell: Dual Aero Chrome	0
8860852	O	Mirror: Dual KW Aero Rear View Motor, heated with Integral CX.	0
8871446	S	Rear Cab Stationary Window 19in x 36in	0
8879917	O	Two Additional Outboard Windows 19in x 12in	10
8890038	O	3.5in x 11.5in Plastic Records Holder: Mounted On Rear Cab Panel. Not available With Sleeper Or 2 Person Bench Seat.	0
8890101	S	One-Piece Bonded-In Windshield With Curved Glass. Standard.	0
8890135	O	Exterior Stainless Steel Sunvisor.	11
8890874	O	Kenworth Cab Air Suspension.	0
<b>8891009</b>	<b>O</b>	<b>Thermal/Sound Insulation Package</b>	<b>0</b>

Sales Code	Std/Opt	Description	Weight
8891011	O	<b>Roof: Raised Profile, Stamped Aluminum w/</b> Additional Head Room & Interior Overhead Storage	0
<b>Lights &amp; Instruments</b>			
9010814	O	<b>Headlamps: LED low beam array, LED high beam,</b> LED turn signal array, LED DRL/Park Lamp, LED side marker/side turn.	8
9020101	S	<b>14-Pin RP170 Body Lighting Connector.</b>	0
9022130	O	<b>Marker Lights: Five Rectangular LED. Chrome</b> housing. For use with raised roof only. Required with exterior sunvisor.	0
9030052	S	<b>LED Stop,Turn,Tail: With Two LED</b> Backup Lights and With An LED License Plate.	0
9042545	O	<b>KW Fog Lights (2) Recessed in Bumper</b>	2
9080206	O	<b>Switch &amp; Wiring: Customer-Installed Beacon Lights</b> with additional 20 ft jumper harness shipped loose.	1
9090027	O	<b>Headlamps to Turn on When Wipers are Active.</b>	0
9090180	O	<b>Backup Alarm: Tail Light Bracket Mounted Variable</b> self-adjusting 82-102 DBA.	0
9090312	O	<b>Body Builder Lighting Harness Coiled End Of Frame</b> For Additional Customer Installed Exterior Lighting. Harness Includes Circuits for Additional Customer Installed Tail Lamps, Turn Lamps, Stop Lamps, and Marker Lamps.	0
<b>Air Equipment</b>			
9101218	S	<b>Air Dryer: Bendix AD-HF Puraguard Heated</b>	0
9108001	S	<b>Moisture Ejection Valve W/ Pull Cable Drain.</b>	0
9140020	S	<b>Nylon Air Tubing in Frame &amp; Cab, Excluding Hoses</b> subject to excessive heat or flexing.	0
9150170	O	<b>Air Tanks: Aluminum Replacing Steel All Tanks.</b> *Not air tanks on lift axles.	-44
<b>Extended Warranty</b>			
9200007	S	<b>Base Warranty - PACCAR PX-7 Engine</b> 36 months / Unlimited miles & km / Unlimited hours.	0
9200022	S	<b>Base Warranty - Standard Service Medium Duty</b> 12 months / Unlimited miles & km	0
9220001	O	<b>Base Warranty: Emissions</b> 5YR/100K MI	0
<b>Miscellaneous</b>			
9409852	O	<b>GHG Secondary Manufacturer: Does Not Apply</b>	0
9490206	O	<b>Warning Triangle Reflector Kit: Shipped Loose.</b> Kit consists of 3 triangles in plastic carrying case. Not floor mounted.	4
9490404	O	<b>One 5 lb. Dry Chemical Type Fire Extinguisher</b>	11

Sales Code	Std/Opt	Description	Weight
		mounted outboard of driver seat. Class ABC.	
9491652	S	<b>EMUX Architecture</b>	<b>0</b>
<b>Promotions</b>			
9511431	O	<b>Model Year 2026 Engine</b>	<b>0</b>
<b>Paint</b>			
9700000	O	<b>Paint Color Number(s).</b>	<b>0</b>
		N9702 A - 03Q FED 17925 WHITE N9720 FRAME N0001 BLACK	
9943004	S	<b>Bumper Unpainted</b>	<b>0</b>
9943050	S	<b>Day Cab Standard Paint</b>	<b>0</b>
9944820	S	<b>1 - Color Paint - Day Cab</b> Color will be White if no other color is specified.	<b>0</b>
9960003	O	<b>Non-Standard Paint Color.</b>	<b>0</b>
9965510	S	<b>Base Coat/ Clear Coat.</b> The Kenworth Color Selector contains additional instructions, as well as information on Kenworth paint guidelines and surface finish applications. Kenworth is standard with Dupont Imron Elite paint.	<b>0</b>

### Special Requirements

Special Requirement 1 0098025

Special Requirement 2

Special Requirement 3

Special Requirement 4

### Order Comments



<b>Total List Price (W/O Freight &amp; Warranty &amp; Surcharges )</b>	\$145,662
<b>Marketing and Service Support Fee</b>	\$995
<b>Prepaid Freight</b>	\$3,925
<b>Total Surcharge/Options Not Subject To Discount</b>	\$0
<b>Total Weight (lbs)</b>	11,034

Any price increase as the result of force majeure, rising costs of components (including but not limited to material shortages) or government tariffs are not included in the quoted price and will be the financial responsibility of the customer.

**Prices and Specifications Subject to Change Without Notice.**

---

Unpublished options may require review/approval.  
Dimensional and performance data for unpublished options may vary from that displayed in CRM.

---

**PRICING DISCLAIMER**

*While we make every effort to maintain the web site to preserve pricing accuracy, prices are subject to change without notice. Although the information in this price list is presented in good faith and believed to be correct at the time of printing, we make no representations or warranties as to the completeness or accuracy of this information. We reserve the right to change, delete or otherwise modify the pricing information which is represented herein without any prior notice. We carefully check pricing specifications, but occasionally errors can occur, therefore we reserve the right to change such prices without notice. We disclaim all liability for any errors or omissions in the materials. In no event will we be responsible for any damages of any nature whatsoever from the reliance upon information from these materials. Please check your order prebills to confirm your pricing information*



**Shipping Destinations**

**Intermediate Destination:**

Final Destinations	Quantity
--------------------	----------